



DIGIDISH 45 with Universal-Twin-LNB, incl. on-pipe fitting

Thanks to its ingenious reflector design the reception performance of the DigiDish 45 is better than with many 60 cm mirrors - and that is with a far lower size of reflector.

EAN	Item no.	Colour	Weight (Box)	Weight
4019588053823	1045/3882	beige	3,7 kg	2,9 kg
4019588353824	1345/3882	slate/grey	3,7 kg	2,9 kg
4019588443822	1445/3882	brick/red	3,7 kg	2,9 kg
4019588543829	1545/3882			
4019588753822	1745/3882	polar/white	3,7 kg	2,9 kg

TOP FEATURES

Only 45 cm small
1 or 2 participants

1 orbital position (for example Astra 19.2 ° East)
Especially suitable for balcony installation
/ Ideal for the city

Ideal for ground and wall mounting
incl. on-pipe fitting

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,7 GHz

LNB CONTROL

Vertical : 11,5 - 14 V

Horizontal : 16 - 19 V

Band switch : 22 kHz

GENERAL CHARACTERISTICS

Material : Aluminium

Material strength : 1 mm

Coating : Powder-coated on both sites

including Wall bracket : Yes

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,7 dB max.

Upper frequency range : 0,7 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 - 1.950 MHz

High band : 1.100 - 2.150 MHz

POWER SUPPLY

LNB voltage supply : 11,5 ... 19 V

Power consumption : max. 190 mA

TECHNICAL DATA

F/D : 0,6

Offset angle : 30 °

Gain : 32,2 dBi @11,3 GHz

Feed reception : 40 mm

SCOPE OF DELIVERY

Satellite Dish
LNB
Screws
Tool
On-pipe fitting
Wall Mount
Installation instructions