



SATMAN 65 PLUS with UNYSAT-V/H-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588069800	beige	2065/9800	6,4 kg	4 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588369801	slate/grey	2365/9800	6,4 kg	4 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588469808	brick/red	2465/9800	6,4 kg	4 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588679801	polar/white	2765/9800	6,4 kg	4 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588569805	yellow with Smiley	2565/9800	6,4 kg	4 kg	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm

TOP FEATURES

65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
1 Teilnehmer

1 Orbitposition (z. B. Astra 19,2° Ost)
Optimal für Wand- und Dachmontage

LNB mit Wetterschutzgehäuse

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

GENERAL CHARACTERISTICS

Material : Aluminium

Material strength : 1,5 mm

Coating : Powder-coated on both sites

Colour *: beige, slate-grey, brick-red, green

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,6 dB max.

Upper frequency range : 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 1

TECHNICAL DATA

Rated measurement : 0,65 m

F/D : 0,69

G/T : 14,5

Offset angle : 27 °

Gain : 35,7 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL
bracket mount, UNYSAT-V/H-LNB, screws,
installation instructions

* black/white