



## SATMAN 65 PLUS with 40 mm Quattro-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.
4019588488007	beige	2065/4880
4019588488038	slate-grey	2365/4880
4019588488700	polar white	2765/4880
4019588488045	brick-red	2465/4880
4019588488052	yellow with Smiley	2565/4880

### TOP FEATURES

For multiple participants

1 orbital position (for example Astra 19.2° East)

Ideal for wall and roof mounting

For distribution to multiple participants on demand, TechniSat distribution elements are required

<b>LOCAL OSCILLATOR</b>	Upper frequency range : 0.6 dB max.	Gain : 35.7 dBi @11,3 GHz
Low band : 9.75 GHz	<b>OUTPUT FREQUENCY RANGE</b>	Mast Ø : 65 mm max.
High band : 10.7 GHz	Low band : 950 ... 1950 MHz	Feed reception : for UNYSAT-Universal-LNB
<b>LNB CONTROL</b>	High band : 1100 ... 2150 MHz	<b>SCOPE OF DELIVERY</b>
Vertical : 11,5 - 14,5 V	<b>PREPARED FOR</b>	Satellite dish antenna SATMAN 65, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions
Horizontal : 16 - 19 V	Number of orbit positions : 1	
<b>INPUT FREQUENCY RANGE</b>	<b>TECHNICAL DATA</b>	
Low band : 10.7 ... 11.7 GHz	Rated measurement : 0.65 m	
High band : 11.7 ... 12.75 GHz	F/D : 0.69	
<b>NOISE FACTOR</b>	G/T : 14.5 dB/K	
Lower frequency range : 0.6 dB max.	Offset angle : 27 °	