



SATMAN 65 PLUS with 40 mm Quattro-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.	Device (W x H x D)	Box
4019588488007	beige	2065/4880	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588488038	slate/grey	2365/4880	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588488700	polar/white	2765/4880	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588488045	brick/red	2465/4880	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm
4019588488052	yellow with Smiley	2565/4880	68 x 76 x 5,8 cm	69,2 x 77,8 x 19,5 cm

TOP FEATURES

65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
Inkl. 40 mm Quattro-LNB

Ausgelegt für viele Teilnehmer, Verteilung erfolgt durch Multischalter oder TECHNIROUTER
1 Orbitposition (z. B. Astra 19,2° Ost)

Optimal für Wand- und Dachmontage

LOCAL OSCILLATOR

Low band : 9,75 GHz
High band : 10,7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V
Horizontal : 16 - 19 V

GENERAL CHARACTERISTICS

Material : Aluminium
Material strength : 1,5 mm
Coating : Powder-coated on both sites
Colour * : beige, slate-grey, brick-red, green

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz
High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,6 dB max.

Upper frequency range : 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz
High band : 1.100 ... 2.150 MHz

PREPARED FOR

Number of orbit positions : 1

TECHNICAL DATA

Rated measurement : 0,65 m
F/D : 0,69
G/T : 14,5

Offset angle : 27 °

Gain : 35,7 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions

* black/white