



SATMAN 65 PLUS with 40 mm Quatt-Switch-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.
4019588489004	beige	2065/4890
4019588489035	slate-grey	2365/4890
4019588489707	polar white	2765/4890
4019588489042	brick-red	2465/4890
4019588489059	yellow with Smiley	2565/4890

TOP FEATURES

65 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
Inkl. 40 mm Quattro-Switch-LNB

1 bis 4 Teilnehmer
1 Orbitposition (z. B. Astra 19,2° Ost)

Optimal für Wand- und Dachmontage

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range : 0.6 dB max.

Upper frequency range : 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 4

TECHNICAL DATA

Rated measurement : 0.65 m

F/D : 0.69

G/T : 14.5 dB/K

Offset angle : 27 °

Gain : 35.7 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions