



SATMAN 850 PLUS with UNYSAT-Twin-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 85 cm Ø

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588089822	beige	6085/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588289826	fir green	6285/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588389823	slate grey	6385/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588489820	brick red	6485/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588789821	polar white	6785/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm
4019588589827	yellow with Smiley	6585/9882	8,8 kg	5,2 kg	89 x 85 x 7,5 cm	92,75 x 88 x 23,5 cm

TOP FEATURES

85 cm dish made of first-class aluminum (powder-coated on both sides)

1 or 2 users

1 orbit position (e.g. Astra 19.2 ° East)

Ideal for wall and roof mounting

LNB with weatherproof housing

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,6 dB max.

Upper frequency range : 0,6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 2

TECHNICAL DATA

Rated measurement : 0,85 m

F/D : 0,67

G/T : 17,2

Offset angle : 21 °

Gain : 38,2 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 850, AZ/EL
bracket mount, LNB in weather-proof
housing, screws, installation instructions

Testurteil(e) SATMAN 850 PLUS with UNYSAT-Twin-LNB



Zweiter Platz in der
Kategorie Sat-Anlagen bei
der Leserwahl zum König-
Kunde-Award 2014
(Camping, Cars & Caravans)



Note: Gut | 88,7 %
SATVISION (04/2012)