



SATMAN 850 PLUS with UNYSAT-Quattro-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 85 cm Ø

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588828827	6285/8880	fir/green	8.8 kg	5.2 kg	85.00 x 87.00 cm	88.00 x 95.00 x 24.00 cm
4019588848887	6485/8880	brick/red	8.8 kg	5.2 kg	85.00 x 87.00 cm	88.00 x 95.00 x 24.00 cm
4019588858879	6785/8880	polar/white	8.8 kg	5.2 kg		
4019588855885	6585/8880	yellow with Smiley	8.8 kg	5.2 kg	85.00 x 87.00 cm	87.00 x 95.00 x 24.00 cm

TOP FEATURES

For multiple participants

1 orbital position (for example Astra 19.2° East)

Ideal for wall and roof mounting

For distribution to multiple participants on demand, TechniSat distribution elements are required

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range : 0.6 dB max.

Upper frequency range : 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

PREPARED FOR

Number of orbit positions : 1

TECHNICAL DATA

Rated measurement : 0.85 m

F/D : 0.67

G/T : 17.2 dB/K

Offset angle : 21 °

Gain : 38.2 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : pour UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 850, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions

UNYSAT Universal Quattro-LNB

Testurteil(e) SATMAN 850 PLUS with UNYSAT-Quattro-LNB



Zweiter Platz in der Kategorie Sat-Anlagen bei der Leserwahl zum König-Kunde-Award 2014 (Camping, Cars & Caravans)



Note: Gut | 88,7 %
SATVISION (04/2012)