



## TECHNIPOLAR 2 M

Mobile air conditioning unit for cooling, with a fan and dehumidifier function - for rooms up to 40 m<sup>2</sup>.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588061026	white	0000/6102	38 kg	33,5 kg	45 x 74,5 x 39,6 cm	49,9 x 88 x 45,9 cm

### TOP FEATURES

3 in 1: Cool. Dehumidify and ventilate

Easy transport with 360 ° castors

Controllable via remote control

LED display

Washable dust filter

Cooling capacity of 12,000 BTU / h (3.5 kW) for rooms up to 40 m<sup>2</sup>

Clearly designed control elements for easy close-up operation

24-hour timer and sleep function

3 speed levels

### SONSTIGES

sVers\_standby\_bereitschaft : 0,5 W

sVers\_standby\_bereitschaft\_wo\_tempreglerr : - W

### COOLING / HEATING CHARACTERISTICS

Cooling performance : 12.000 Btu/h

Cooling performance : 3,5 kW

Modes : Cooling, fan, dehumidifier, timer

Temperature range : 18 - 32 °C

Room size : Bis zu 40 m<sup>2</sup> (104m<sup>3</sup>)

Dehumidification performance : 32 l/d

Air circulation : 350 - 460 m<sup>3</sup>/h

Volume : 54 - 64 dB

Coolant : R290 (250g)

GWP coolant : 3

Power consumption - cooling : 1,2 kW-h (5,1 A)

ERR : 3,1 (Refrigeration factor)

Energy efficiency class - cooling : A+

Intake pressure : 1,2 MPa

Outlet pressure : 2,3 MPa

Exhaust hose length : 1,5 m

Exhaust hose diameter : 15 cm

### POWER AND ENERGY CONSUMPTION (EU) 626/2011

Energy class : A+

### AMBIENT OPERATING CONDITIONS

IP class : X 0

### DISPLAY

Type : 7 segments, 2 digits

### GENERAL CHARACTERISTICS

Colour \*: white

Cable length : 1,5 m

### POWER CONSUMPTION

Energy class : A+

Standby : 0,5 W

### POWER SUPPLY

Mains adapter : internal

Effective output : 1.350 W

Frequency : 50 Hz

Nominal voltage : 220 ... 240 V

### SENSOR

Temperature sensor : Yes

### SCOPE OF DELIVERY

Mobile air conditioning unit, operating instructions, remote control, exhaust air and condensate hose, window seal for standard casement windows (circumferential length 400 cm, width 40 cm)

\* black/white