



## DIGISPLITTER CE 4 S/T HD

Quad splitter for distribution or combination of satellite, terrestrial and cable TV, as well as radio signals

EAN	Colour	Item no.
4019588079144	silber	0000/7914

### TOP FEATURES

DC power pass

### DECOUPLING

5 - 862 MHz : Typ. 20 dB (< 40 MHz = 8 dB)

950 - 1750 MHz : Typ. 20 dB

1750 - 2150 MHz : Typ. 20 dB

### RETURN LOSS

5 - 862 MHz : Typ. 12 dB

950 - 1750 MHz : Typ. 12 dB

1750 - 2150 MHz : Typ. 10 dB

### TECHNICAL DATA

Input : 1

Outputs : 4

Frequency range : 5 ... 2.400 MHz

Shielding factor :  $\geq 75$  dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz : Typ. 8,5 dB ( $\pm 1$ )

950 - 1750 MHz : Typ. 9,5 dB ( $\pm 1,5$ )

1750 - 2150 MHz : Typ. 10,5 dB ( $\pm 2$ )

### SCOPE OF DELIVERY

4-way TV Sat splitter