



UNYSAT Universal-Quattro-LNB

Digital LNB for multi-switch distribution

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588108806	grey	0010/8880	420 g	366 g	13.50 x 14.50 x 6.00 cm	15.00 x 17.00 x 7.50 cm

TOP FEATURES

For multi-switch distribution

Special weatherproof housing for the excellent receiving electronics

Suitable for all TechniSat SATMAN dishes

Quick and easy assembly without a retaining clamp

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2.5 MHz

Phase noise : -85 @10kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0.75 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

LNB voltage supply : 11.5 ... 19 V

Power consumption : 200 mA

PREPARED FOR

Number of orbit positions : 1

TECHNICAL DATA

Outputs : 4

Impedance : 75 Ω

Connector type : F female

Feed reception : For SATMAN

Amplification : 60 ... 67 dB

Skew : -20 ... 20 °

SCOPE OF DELIVERY

Universal-Quattro-LNB