



UNIX Twin LNB

High-quality twin converter for satellite installations with two receivers

EAN	Colour	Item no.
4019588768024	beige/orange	76-4802-00

TOP FEATURES

Top-class reception performance for HD and UHD signals

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Ideal for a TWIN decoder

Low power consumption

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

LNB CONTROL

Vertical : 10,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 70 °C

Humidity : 10 ... 90 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0,1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply : 10,5 ... 19 V

Power consumption : max. 150 mA

TECHNICAL DATA

Outputs : 2

Feed reception : 40 mm

Impedance : 75 Ω

Amplification : 55 dB

Connector type : F-Buchse