



UNiX Quad Gold

High-quality Quad LNB for satellite installations with four receivers

EAN	Colour	Item no.
4019588768147	beige/orange	76-4814-00

TOP FEATURES

Top-class reception performance for HD and UHD signals

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Ideal for installations with two TWIN receivers

Up to 4 users

Low power consumption

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

LNB CONTROL

Vertical : 10,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 70 °C

Humidity : 10 ... 90 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0,1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply : 10,5 ... 19 V

Power consumption : max. 180 mA

TECHNICAL DATA

Outputs : 4

Feed reception : 40 mm

Impedance : 75 Ω

Connector type : f-connector

Amplification : 55 dB