



Universal-V/H-LNB with satellite finder

Digital LNB with 1 legacy output and satellite finder

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588198944	black	0019/8194	120 g	102 g	12,9 x 5,7 x 5,7 cm	14 x 6,3 x 6,3 cm

TOP FEATURES

For 1 participant	Feed-ø 40 mm	LTE interference-safe
F connectors	Integrated level meter and compass	Optimised for camping: Quick alignment thanks to integrated level meter and compass

LOCAL OSCILLATOR	OUTPUT FREQUENCY RANGE
Low band : 9,75 GHz	Low band : 950 ... 1.950 MHz
High band : 10,6 GHz	High band : 1.100 ... 2.150 MHz
Accuracy : ± 1 MHz	POWER SUPPLY
Temperature drift : ± 2,5 MHz	LNB voltage supply : 12 ... 20 V
Phase noise : -75 @10kHz	Power consumption : max. 150 mA
LNB CONTROL	TECHNICAL DATA
Vertical : 12 ... 14,5 V	Outputs : 1
Horizontal : 16 ... 20 V	Feed reception : 40 mm
Band switch : 22 kHz	Amplification : 56 ... 65 dB
AMBIENT OPERATING CONDITIONS	Impedance : 75 Ω
Ambient temperature : -10 ... 60 °C	Connector type : F
Humidity : 10 ... 95 %	SCOPE OF DELIVERY
HANDLING/COMFORT	UNYSAT Universal-V/H-LNB with satellite finder
SAT-Finder : Yes	
INPUT FREQUENCY RANGE	
Low band : 10,7 ... 11,9 GHz	
High band : 11,7 ... 12,75 GHz	
NOISE FACTOR	
Noise figure : typ. 0,9 dB	