



## IEC antenna cable

Antenna cable with male and female IEC connectors packed in blister

| EAN           | Item no.   |
|---------------|------------|
| 4019588783010 | 76-4830-01 |
| 4019588783034 | 76-4830-03 |
| 4019588783058 | 76-4830-05 |
| 4019588763111 | 76-4831-01 |
| 4019588763135 | 76-4831-03 |
| 4019588763159 | 76-4831-05 |

### TOP FEATURES

Innenleiter aus massivem hochreinen Elektrolytkupfer!

Braid made of aluminum

#### ATTENUATION

45 MHz : 8,2

100 MHz : 9,5

200 MHz : 10,8

450 MHz : 14,8

800 MHz : 20,1

1000 MHz : 21,5

1750 MHz : 29

2250 MHz : 33,5

#### TECHNICAL DATA

Frequency range : 5 ... 2.250 MHz

Impedance : 75  $\Omega$  ( $\pm$  3)

Inner cable diameter : 102 mm (18AWG)

Inner cable material : CCS (OFC)

Isolation : Zell-PE

Diameter dielectric : 4,65 mm ( $\pm$  0,1)

Outer cable : 1x aluminum foil + 1x aluminum braid

Sheath : PVC

Diameter with coating : 6,8 mm ( $\pm$  0,2)

Bending radius :  $\geq$  35 mm

#### SCOPE OF DELIVERY

Antenna cable with male and female IEC connectors packed in blister<br>