



IEC antenna cable

Antenna cable with male and female IEC connectors packed in blister

EAN	Item no.
4019588783010	76-4830-01
4019588783034	76-4830-03
4019588783058	76-4830-05
4019588763111	76-4831-01
4019588763135	76-4831-03
4019588763159	76-4831-05

TOP FEATURES

Innenleiter aus massivem hochreinen Elektrolytkupfer!

Braid made of aluminum

ATTENUATION

45 MHz : 8,2

100 MHz : 9,5

200 MHz : 10,8

450 MHz : 14,8

800 MHz : 20,1

1000 MHz : 21,5

1750 MHz : 29

2250 MHz : 33,5

TECHNICAL DATA

Frequency range : 5 ... 2.250 MHz

Impedance : 75 Ω ($\pm$ 3)

Inner cable diameter : 102 mm (18AWG)

Inner cable material : CCS (OFC)

Isolation : Zell-PE

Diameter dielectric : 4,65 mm ($\pm$ 0,1)

Outer cable : 1x aluminum foil + 1x aluminum braid

Sheath : PVC

Diameter with coating : 6,8 mm ($\pm$ 0,2)

Bending radius : $\geq$ 35 mm

SCOPE OF DELIVERY

Antenna cable with male and female IEC connectors packed in blister
