



## IEC angular antenna cable

Antenna cable terminated with male and female angular IEC connectors, packed in blister

| EAN           | Colour | Item no.   |
|---------------|--------|------------|
| 4019588763210 | weiß   | 76-4832-01 |
| 4019588763234 | weiß   | 76-4832-03 |

### TOP FEATURES

Inner copper conductor (CCS)

Braid made of aluminum

### ATTENUATION

45 MHz : 8,2

100 MHz : 9,5

200 MHz : 10,8

450 MHz : 14,8

800 MHz : 20,1

1000 MHz : 21,5

1750 MHz : 29

2250 MHz : 33,5

### TECHNICAL DATA

Frequency range : 5 ... 2.250 MHz

Impedance : 75  $\Omega$  ( $\pm$  3)

Inner cable diameter : 102 mm (18AWG)

Inner cable material : CCS (OFC)

Isolation : Physically foamed PE

Diameter dielectric : 4,65 mm ( $\pm$  0,1)

Outer cable : 1x aluminum foil + 1x aluminum braid

Sheath : PVC, white

Diameter with coating : 6,8 mm ( $\pm$  0,2)

Bending radius :  $\geq$  35 mm

### SCOPE OF DELIVERY

Antenna cable terminated with male and female angular IEC connectors, packed in blister<br>