



DIGIDISH 45 with sat finder V/H-LNB

Thanks to its ingenious reflector design the reception performance of the DigiDish 45 is better than with many 60 cm mirrors - and that is with a far lower size of reflector.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588041950	beige	1045/8195	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588341951	slate grey	1345/8195	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588441958	brick red	1445/8195	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588541955	yellow with Smiley	1545/8195	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588741959	polar white	1745/8195	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm

TOP FEATURES

Only 45 cm small
1 participant

1 orbital position (for example Astra 19.2° East)

Ideal for ground and wall mounting

Especially suitable for balcony installation
/ Ideal for the city

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2.5 MHz

Phase noise : -75 @10kHz

LNB CONTROL

Vertical : 12 - 14.5 V

Horizontal : 16 - 20 V

Band switch : 22 kHz

HANDLING/COMFORT

SAT-Finder : Yes

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Noise figure : typ. 0.9 dB

OUTPUT FREQUENCY RANGE

Low band : 950 - 1950 MHz

High band : 1100 - 2150 MHz

POWER SUPPLY

LNB voltage supply : 12 ... 20 V

Power consumption : max. 150 mA

PREPARED FOR

Number of orbit positions : 1

Number of clients : 1

TECHNICAL DATA

Rated measurement : 0.45 m

F/D : 0.6

Offset angle : 30 °

Gain : 32.2 dBi @11,3 GHz

Feed reception : 40 mm

SCOPE OF DELIVERY

Satellite dish 45 cm, LNB, wall bracket,
screws, tool, mounting instruction