



## TECHNIVISION 32 HD

Full-HD Digital TV with eLED panel and HDTV multituner including digital DVR function via USB to record TV and radio broadcast on an external hard drive

EAN	Weight without stand	Item no.	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588327320	9 kg	5032/7326	black	13.3 kg	9.6 kg	779 x 523 x 48 mm	77.90 x 57.40 x 20.50 cm	85.50 x 66.00 x 25.00 cm
4019588327306	9 kg	5032/7306	silver/black	13.3 kg	9.6 kg	779 x 523 x 48 mm	77.90 x 57.40 x 20.50 cm	85.50 x 66.00 x 25.00 cm

### TOP FEATURES

HDTV multituner

Digital video recorder function via USB (DVRready)

Timeshift (in conjunction with an external storage medium)

PerfectRecording

LED display with clock

Common Interface Plus (CI+)

### AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 - 35 °C

Humidity : 10 - 75 %

### LNB CONTROL

Vertical : <14 V without load, > 11.5 V at 400 mA V

Horizontal : <20 V without load, > 17.2 V at 400 mA V

Band switch : 22 kHz

Current consumption : max (kurzschlussfest) 400 mA

DiSEqC : DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router

### TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

### AUDIO

AC3 Dolby Digital bitstream out : Yes

Speakers : integrated broadband speaker system

### CONNECTIONS

HDMI (in) : 2

Common Interface Plus (CI+) : Yes

Digital electric audio output : Yes Cinch

Audio in/AUX in : Yes 3.5mm Klinke

VGA : Yes

YUV (component input) : Yes Cinch

Scart : 1 (FBAS/RGB)

S Video : Yes

Video IN : 1 Cinch Composite

F socket : Yes

IEC-Connector : Yes

### DECRYPTION SYSTEM

CI+ : Yes

### DIMENSIONS / WEIGHT

Set width without stand : 779 mm

Set height without stand : 523 mm

Weight without stand : 9 kg

Set depth without stand : 48 mm

<b>DISPLAY</b>	<b>HOTEL MODE</b>	<b>TUNER</b>
Size (cm) : 81 cm	Customisable start screen : Yes	Tuner type : HDTV-Multituner
Frequency : 50 Hz	Configurable on times : Yes	DVB-S tuner : 1
Format : 16:9	Energy card function : Yes	DVB-C Tuner : 1
Contrast ratio : 4.000:1	USB cloning function : Yes	DVB-T Tuner : 1
Brightness : 450 cd/m <sup>2</sup>	Multimedia connectors : Yes	Analogue UHF/VHF/CATV tuner : 1
Response time : 8 ms	Menu locking : Yes	Input impedance : 75 Ω
Angle of view : 176° V / 176° H	Integrated LED clock : Yes	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
Freeze frame : Yes	Radio mode : Yes	TECHNIROUTER ready : Yes
Resolution (vertical and horizontal) : 1920 x 1080	Mixing of channel slots : Yes	<b>TUNER - ANALOGUE</b>
Size (inches) : 32	Multicode remote control : Yes	Reception range : 47 ... 862 MHz
720p : Yes	Fireproofed housing : Yes	Video standards : B/G stereo, D/K mono, L/L'
HD : Yes	<b>MATERIALS CONTAINED</b>	<b>TUNER - CABLE</b>
1080i : Yes	Lead : Yes	Reception range : 51 ... 858 MHz
SD : Yes	<b>OTHER FEATURES</b>	FEC : Reed-Solomon
Type : Full-HD eLED	OSD languages : Polish, Dutch, Spanish, Swedish, Portuguese, Turkish, Czech, Hungarian, Greek, French, English, Italian, Russian, German	Demodulation : 16/32/64/128/256 QAM
<b>HANDLING/COMFORT</b>	Total programme memory : 5000	Symbol rate : 1.7 ... 7 Mbaud
Alarm : Yes	Regional channel selection : Yes	<b>TUNER - SAT</b>
Clock : Yes	<b>POWER SUPPLY</b>	FEC : Viterbi and Reed-Solomon
Sleep timer : Yes	Frequency : 50 Hz	DVB-S : 2 ... 45 Mbaud
	Mains adapter : internal	DVB-S2 : 10 ... 31 Mbaud
	Nominal voltage : 230 V	Reception range : 950 ... 2150 MHz
	<b>SUPPORTED FORMATS &amp; CODECS</b>	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
	MPEG-2 : Yes	DVB-S : QPSK
	Video-Formats : TS4, TS, VOB	DVB-S2 : 8PSK - QPSK
	JPEG : Yes	<b>TUNER - TERRESTRIAL</b>
	MP3 : Yes	Reception range 1 : 174 ... 230 MHz
		Voltage supply : 5 V
		Demodulation : COFDM
		Bitrate : 4 ... 32
		Power supply : 0.05 A
		Reception range 2 : 470 ... 860 MHz
		Transmission mode : 2k/8k
		<b>WALL BRACKET</b>
		VESA wall mounting standards : VESA 200 x 100
		<b>SCOPE OF DELIVERY</b>
		TechniVision 32 HD, Stand, 230 V mains power cable, TechniControl remote control incl. batteries, Manual