



## TECHNISMART door/window contact

Door/Window contact switch to proof if the door resp. the window is closed or not for TECHNISMART 1.

EAN	Colour	VPE Palette	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588095625	Weiß	0	0000/9562	60 g	32 g	8,5 x 2,5 x 2,5 cm	10,6 x 2,5 x 5,5 cm

### TOP FEATURES

Magnetic door/window contact

Theft and tamper protection

Simple connection via TECHNISMART App

433,92 MHz wireless technology

Detecting the closing state of doors or windows

Component for the TECHNISMART 1 alert system

Cordless battery operation

Compact, discreet design

### WLAN

WLAN : Ja (802.11ac)

### AMBIENT OPERATING CONDITIONS

Ambient temperature : -10 ... 45 °C

Humidity : 10 ... 75 %

### BLUETOOTH VERSION & PROFILE

Bluetooth version : 5

### CONNECTIONS

Ethernet 10/100 (RJ-45) : Yes

DC IN : 1

USB : 2

### FUNK COMMUNICATION

Telecommunication : RF (ISM-Band)

Range inside : max. 30 m

Range outside : max. 100 m

operating frequency : 433,92 MHz

### NETWORK & COMMUNICATION

Bluetooth : Yes 4.1 LE

### OPERATION POSSIBILITIES

Tablet PC : Ja

Smartphone : Ja

### OTHER FEATURES

OSD languages : English, German

### POWER SUPPLY

Nominal voltage : 3 V

Battery life : up to 120 min pro Akkuladung auf niedrigster Stufe

Frequency : 50 Hz

Rechargeable battery : Lithium ions with 14,4 V, 2.600 mAh und 37,44 Wh

Mains adapter : DC 18 V / 3.300 mA

Effective output : 3 W

Non rechargeable battery : CR123A

Type of power supply : External

### SCOPE OF DELIVERY

Door/Window contact, installation material