



## UNIX Quattro LNB

A universal LNB converter designed for installation with a multiswitch

EAN	Colour	Item no.	Weight
4019588768031	beige/orange	76-4803-00	196 g

### TOP FEATURES

Top-class HD and UHD signal reception performance

Simple and quick assembly

High quality housing resistant to difficult weather conditions

Very low noise figure

Perfect for installations with two TWIN decoders

For multiswitch installations

Low power consumption

### LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

### LNB CONTROL

Vertical : 10,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

### AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 70 °C

Humidity : 10 ... 90 %

### INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

### NOISE FACTOR

Noise figure : 0,1 dB

### OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

### POWER SUPPLY

LNB voltage supply : 10,5 ... 19 V

Power consumption : max. 180 mA

### TECHNICAL DATA

Outputs : 4

Impedance : 75 Ω

Amplification : 55 dB

Feed reception : 40 mm

Connector type : F connector

### SCOPE OF DELIVERY

UNIX Quattro LNB