



## DIGISPLITTER CE 3 HD

For 3-fold distribution or connection of satellite, terrestrial TV, cable and radio signals. The distributor has a constant tension grommet.

EAN	Colour	Item no.
4019588769939	silber	76-4993-00

### TOP FEATURES

DC power pass

### DECOUPLING

5 - 862 MHz : Typ. 22 dB (< 40 MHz = 8 dB)

950 - 1750 MHz : Typ. 20 dB

1750 - 2150 MHz : Typ. 20 dB

### RETURN LOSS

5 - 862 MHz : Typ. 12 dB

950 - 1750 MHz : Typ. 12 dB

1750 - 2150 MHz : Typ. 10 dB

### TECHNICAL DATA

Input : 1

Outputs : 3

Frequency range : 5 ... 2.400 MHz

Shielding factor :  $\geq 75$  dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz : Typ. 4,5 dB ( $\pm 1$ )

950 - 1750 MHz : Typ. 5 dB ( $\pm 1,5$ )

1750 - 2150 MHz : Typ. 6 dB ( $\pm 2$ )

### SCOPE OF DELIVERY

3-way satellite TV splitter<br>