Heating thermostate 3

Radiator thermostat for controlling the temperature of radiators in hot water heating systems

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588095298	Weiß	0000/9529	234 g	158 g	6,2 x 6,8 x 8,3 cm	10,5 x 6,5 x 13 cm

TOP FEATURES

Integration/control with TechniSat CONNECT

For using with water based room radiators

temperature indicator in the display

LED signaling for interactive operation

Real-Time Control (FLiRS)

Adapters for Danfoss valves

AMBIENT OPERATING CONDITIONS

IP class : 20

Ambient temperature : 0 bis 40 °C

FUNK COMMUNICATION

Telecommunication : Z-Wave Plus

Range inside : max. 40 m

operating frequency : 868,42 MHz

OTHER FEATURES

Battery change indicator : Yes

POWER SUPPLY

Nominal voltage : 3 V

Non rechargeable battery : 2 x 1.5 V AA alkaline, class III

SENSOR

Sensor type : Programmable electronic radiator thermostat

Standard area : 8 - 28 °C

SCOPE OF DELIVERY

Heating thermostat 3, adapter for Danfoss valves (RA/RAV/RAVL), screw for adapter, 2 alkaline batteries AA, instruction manual

TechniSat