



TECHNIROUTER MINI 2/1x2

Expand an existing cable derivation into a Twin solution or into a two-subscriber solution without laying additional cables

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032897	silver/yellow	0000/3289	400 g	200 g	5.00 x 2.80 x 11.50 cm	18.00 x 4.00 x 18.50 cm

TOP FEATURES

Expansion of coaxial line to twin function

No additional cable routing required

2 adjustable orbit positions

Very compact dimensions

Can be connected behind Twin, Quatro Switch LNB and multiswitch

Terrestrial outlet for DVB-T(2)/UHV

AMBIENT OPERATING CONDITIONS

Humidity: 10 ... 75 %

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: 2 dB

Terrestrial: -3 dB

DECOUPLING

Trunks: 30 dB

POWER CONSUMPTION

In operation: max. 2 W (Standby 0 W)

POWER SUPPLY

Nominal voltage: 230 V

Frequency: 50 Hz

Mains adapter: external 12 VDC/1,5 A

RECEPTION RANGE

Sat: 950 ... 2150 MHz

Terrestrial: 47 ... 862 MHz

SINGLE-CABLE OUTPUT

Output frequency: 47 ... 2150 MHz

Number of output channels: 2

Frequency of the output channels: 1284, 1400 MHz

Frequency SAT: 1250 ... 1430 MHz

Frequency DVB-T: 47 ... 862 MHz

Output level: -3 dB

TECHNICAL DATA

Satellite inputs: 2

Number of cable connections: 1

Subscribers per cable: 2

SCOPE OF DELIVERY

TechniRouter Mini 2/1x2, Manual

Testurteil(e) TECHNIROUTER MINI 2/1x2



SAT Empfang (02/2012)



Satvision (10/2012)