



DIGIT ISIO S1

HDTV digital satellite receiver with twin tuner, digital video recorder and Internet functionality via USB to record TV and radio programs on an external hard drive

EAN	Colour	Item no.	Hard drive	Weight (Box)	Weight	Device (W x H x D)	Box
4019588147539	silver	0001/4753	extern	2,9 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm

TOP FEATURES

HDTV tuner (DVB-S/S2)

DVRready: Digital video recorder function for recording to USB hard drive

Pay TV compatible via CI+

ISIO: Access to multimedia library, ISIO apps and HbbTV

Easy start-up via AutoInstall

Multimedia streaming on home network (via UPnP)

Electronic program guide (EPG)

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 ... 35 °C

Humidity : 10 ... 75 %

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSeqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HbbTV : Yes

HTML 5 support : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

USB : 3 (USB 2.0)

eSATA : Yes

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes (rechts / links)

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

F socket : 2

DECRYPTION SYSTEM

Conax : Yes

Nagravision : Yes

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

576p : Yes

576i : Yes

720p : Yes

1080i : Yes

SD : Yes

HD : Yes

HANDLING/COMFORT

Sleep timer : Yes

Alarm : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

OTHER FEATURES

OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

Total programme memory : 5.000

Regional channel selection : Yes

POWER CONSUMPTION

Standby fast start : 6,5 W

Standby LED : < 0,2 W

In operation : 11,05 W (ohne LNB-Versorgung)

POWER SUPPLY	TECHNISAT CONNECT	TUNER - SAT
Nominal voltage : 230 V	Control : Yes	Reception range : 950 ... 2.150 MHz
Frequency : 50 Hz	SFI : Yes	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
Mains adapter : internal	TUNER	DVB-S : QPSK
SUPPORTED FORMATS & CODECS	Tuner type : DigitalSat	DVB-S : 2 ... 45
Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX	DVB-S tuner : 2	DVB-S2 : 8PSK-QPSK
Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI	Single Cable Solution (SatCR) : SCR1 = EN50494	DVB-S2 : 10 ... 31
JPEG : Yes	Reception on : HDTV (MPEG-4 & 2), SD (MPEG-2)	FEC : Viterbi and Reed-Solomon
Audio-Formats : AAC, MP3, M4A, MP2	TECHNIROUTER ready : Yes	SCOPE OF DELIVERY
	TECHNISELECT 12 ready : Yes	DIGIT ISIO S1, remote control with batteries, power cable, HDMI cable, instruction manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.