



2 YEARS
WARRANTY

BESSER
MADE IN
GERMANY

ENERGY
SAVER
WITHOUT POWER SUPPLY

TECHNISWITCH 5/8 K

Multi-switch system with connection possibility of 4 levels for distribution to up to 24 participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032583	blue/yellow	0000/3258	374 g	374 g	17.10 x 12.60 x 3.32 cm	17.50 x 18.50 x 3.90 cm

TOP FEATURES

For distribution of one satellite position
Up to 24 subscribers can be connected

For connecting a Quatro LNB
Up to 100 m distribution length due to inclination compensation

Energy saving - no mains adapter for operation
No attenuation in satellite range

AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : -4 ... -2 dB

Terrestrial : 1 ... 4 dB

DECOUPLING

Output : > 35 dB

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Outputs : 8

Distribution length : max. 100 m

TRANSMISSION LOSS

Sat : 2 ... 5 dB

Terrestrial : 2 ... 3 dB

SCOPE OF DELIVERY

TechniSwitch 5/8 K, manual