



DIGICORDER ISIO S1

Digital HDTV satellite receiver with internet functionality

| EAN | Item no. | Colour | Hard drive | Weight (Box) | Weight | Device (W x H x D) | Box |
|-------------------|-----------|--------|---------------|--------------|--------|-------------------------|--------------------------|
| 401958851726 4 | 0501/4726 | silver | 500 GigaByte | 3.3 kg | 2.9 kg | 43.50 x 6.00 x 19.90 cm | 49.00 x 16.00 x 26.00 cm |
| 401958850726 5 | 0500/4726 | black | 500 GigaByte | 3.3 kg | 2.9 kg | 43.50 x 6.00 x 19.90 cm | 49.00 x 16.00 x 26.00 cm |
| 401958811726 6 | 1001/4726 | silver | 1000 GigaByte | 3.3 kg | 2.9 kg | 43.50 x 6.00 x 19.90 cm | 49.00 x 16.00 x 26.00 cm |
| 401958810726 7 | 1000/4726 | black | 1000 GigaByte | 3.3 kg | 2.9 kg | 43.50 x 6.00 x 19.90 cm | 49.00 x 16.00 x 26.00 cm |

TOP FEATURES

UPnP/DLNA/Client- & Server function for home networking

2 CI+ interface (compatible with HD and Sky +)

Free browsing, and HbbTV ISIO Live! (TechniSat Service Portal)

IP module for access to libraries, Video on demand services and apps

Integrated hard drive (1 TB)

HDTV Twin Tuner

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : 5 ... 35 °C

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HTML 5 support : Yes

HbbTV : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes (rechts / links)

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes

F socket : 2

DECRYPTION SYSTEM

Conax : Yes

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

576i : Yes

576p : Yes

SD : Yes

HD : Yes

720p : Yes

1080i : Yes

HANDLING/COMFORT

Sleep timer : Yes

Alarm : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

| OTHER FEATURES |
|--|
| OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian |
| Total programme memory : 5000 |
| Regional channel selection : Yes |
| POWER CONSUMPTION |
| Standby fast start : 6.9 W |
| Standby LED : 0.25 W |
| In operation : 13 W |
| POWER SUPPLY |
| Nominal voltage : 230 V |
| Frequency : 50 Hz |
| Mains adapter : internal |

| SUPPORTED FORMATS & CODECS |
|---|
| Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX |
| Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI |
| JPEG : Yes |
| Audio-Formats : AAC, MP3, M4A, MP2 |

| TUNER |
|---|
| Tuner type : DigitalSat |
| DVB-S tuner : 2 |
| Single Cable Solution (SatCR) : SCR1 = EN50494 |
| Reception on : HDTV (MPEG-4 & 2), SD (MPEG-2) |
| Input impedance : 75 O |
| TECHNIROUTER ready : Yes |
| TECHNISELECT 12 ready : Yes |
| TUNER - SAT |
| Reception range : 950 ... 2150 MHz |
| Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung) |
| DVB-S : QPSK |
| DVB-S : 2 ... 45 |
| DVB-S2 : 8PSK-QPSK |
| DVB-S2 : 10 ... 31 |
| FEC : Viterbi and Reed-Solomon |
| SCOPE OF DELIVERY |
| DigiCorder ISIO S1, remote control including batteries, mains cable, HDMI cable, operating instructions, guarantee card |

Testurteil(e) DIGICORDER ISIO S1



SFT (01/2012)



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.