



**BESSER
MADE IN
GERMANY**

**2 YEARS
WARRANTY**

TECHNISELECT 12

For feeding 12 selectable satellite transponders into a single cable distribution system

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032996	blue/yellow	0000/3299	800 g	500 g	29.20 x 11.20 x 3.10 cm	31.80 x 20.00 x 4.50 cm

TOP FEATURES

Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

Eingang zum Empfang von Terrestrischen Signalen

4 vollwertige Receiverausgänge oder Sat-Stämme

Messausgang -20 dB

Stromsparfunktion

LNB CONTROL

Current consumption : max. 400 mA (für LNB und / oder Verstärker)

Vertical : 13 V über VL

AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

Humidity : 10 ... 75 %

DECOUPLING

Trunks : 30 dB

POWER SUPPLY

Nominal voltage : 230 V

Frequency : 50 Hz

Mains adapter : internal

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 80 ... 790 MHz

SINGLE-CABLE OUTPUT

Output frequency : 80 ... 2150 MHz

Number of output channels : 12

Frequency of the output channels : 974, 1076, 1178, 1280, 1382, 1484, 1586, 1688, 1790, 1892, 1994, 2096 MHz

Frequency SAT : 950 ... 2150 MHz

Frequency DVB-T : 80 ... 790 MHz

Output level : max. 105 dBµV

Output level : 12 ... 20 dB (Einstellbare Verstärkung)

TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Number of cable connections : 1

Subscribers per cable : über 50

TRANSMISSION LOSS

Terrestrial : -20 ... -12 dB (Einstellbare Verstärkung)

SCOPE OF DELIVERY

TechniSelect 12, manual, CD-ROM with TechniSelect Configuration Tool, USB-cable

Testurteil(e) TECHNISELECT 12



Infosat (02/2012)