



MultyVision 46 ISIO

Full-HD eLED Digital Television with Dual HDTV multituner for reception of analogue and digital TV. Integrated IP module for access to internet content and DVR for recording of HD and standard TV as well as radio programmes.

EAN	Weight without stand	Item no.	Hard drive	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
401958884 6067	19,5 kg	5846/0306	1000 GB	silver	34 kg	25 kg	1090 x 713 x 61 mm	109.00 x 76.50 x 22.00 cm	125.00 x 100.00 x 30.00 cm
401958884 6166	19,5 kg	5846/0316	1000 GB	titanium	34 kg	25 kg	1090 x 713 x 61 mm	109.00 x 76.50 x 22.00 cm	125.00 x 100.00 x 30.00 cm

TOP FEATURES

Dual HDTV multituner for receiving DVB-S, DTT and DVB-C incl. HDTV

Integrated DVR (1 TB hard drive) and recording function via external device sources/Timeshift

Elegant and sophisticated design with rotating pedestal

LED time and program display

2x Common Interface (CI+)

UPnP (Universal Plug and Play), incl. DLNA

AMBIENT OPERATING CONDITIONS

Humidity : 10 - 75 %

Ambient temperature : 5 - 35 °C

LNB CONTROL

Band switch : 22 kHz

DiSEqC : DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router

Vertical : <14 V without load, > 11.5 V at 400 mA V

Horizontal : <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V

Current consumption : 400 mA max. kurzschlussfest 400 mA

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HbbTV : Yes

AUDIO

Speakers : 2 x broadband speakers with bass reflex

AC3 Dolby Digital bitstream out : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI (in) : 3 (davon 1 x HDMI Mini Front)

HDMI (out) : 1

Smartcard reader : Yes (Conax)

Digital electric audio output : Yes (Adapter)

Digital optical audio out : Yes (Toslink)

Digital audio in : Yes (Adapter)

Audio out analogue : Yes (3.5mm Klinke)

AV input : Yes (Front)

Audio in/AUX in : Yes (3.5mm Klinke)

VGA : Yes

YUV (component input) : Yes (Adapter)

Scart : 1 (Adapter)

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

IEC-Connector : Yes

DECRYPTION SYSTEM

Conax : Yes
CI+ : Yes
DIMENSIONS / WEIGHT
Set height without stand : 713 mm
Set width without stand : 1090 mm
Set depth without stand : 61 mm
Weight without stand : 19,5 kg
DISPLAY
Size (cm) : 117 cm
Frequency : 200 Hz
Format : 16:9
Contrast ratio : 5.000:1
Picture in Picture (PIP) : Yes (2 x HD, 2 x SD, 1 x SD u. 1 x HD)
Brightness : 450 cd/m²
Response time : 6 ms
Angle of view : 178° / 178°
Picture and Picture (PAP) : Yes (2xHD; 2xSD; 1xSD u. 1xHD)
Freeze frame : Yes
Zoom : Yes
1080i : Yes
720p : Yes
SD : Yes
Type : Full-HD eLED
Size (inches) : 46
HD : Yes
Resolution (vertical and horizontal) : 1920 x 1080
HANDLING/COMFORT
Alarm : Yes
Clock : Yes
Sleep timer : Yes
HOTEL MODE
Customisable start screen : Yes
Configurable on times : Yes
Energy card function : Yes
USB cloning function : Yes
Multimedia connectors : Yes
Menu locking : Yes
Integrated LED clock : Yes
Radio mode : Yes

Mixing of channel slots : Yes
Testurteil(e) MultyVision 46 ISIO
Multicode remote control : Yes

Fi
M
L
O
C
German, Swedish, Hungarian, Russian, Ukrainian, Polish, Greek, French, Spanish, Turkish



Testergebnis: gut | Note: 2,28
AudioVideoFoto (01/2012)

Total programme memory : 5000
Regional channel selection : Yes
POWER SUPPLY
Nominal voltage : 230 V
Frequency : 50 Hz
Mains adapter : internal
SUPPORTED FORMATS & CODECS
Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, VC-1, Theora
Video-Formats : MKV, MP4, MOV, MPG, TS, TS4, VOB, WMV, Xvid, AVI
Picture-Formats : BMP, JPEG, GIF, PNG, TIFF
Audio-Formats : AAC, MP3, FLAC, MP2, OGG
TUNER
DVB-S tuner : 2
DVB-C Tuner : 2
DVB-T Tuner : 2
Analogue UHF/VHF/CATV tuner : 2
Input impedance : 75 Ω
TECHNIROUTER ready : Yes
Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
TECHNISELECT K : Yes
TUNER - ANALOGUE
Reception range : 47 ... 862 MHz
Video standards : B/G stereo, D/K mono, L/L, I
TUNER - CABLE
Symbol rate : 1.7 ... 7 Mbaud
Demodulation : 16 / 32 / 64 / 128 / 256 QAM
FEC : Reed-Solomon
Reception range : 51 ... 858 MHz
TUNER - SAT
DVB-S : QPSK
DVB-S2 : 10 ... 31 Mbaud
Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
DVB-S2 : QPSK - 8PSK
FEC : Viterbi and Reed-Solomon
Reception range : 950 ... 2150 MHz
DVB-S : 1 ... 45 Mbaud
TUNER - TERRESTRIAL
Reception range 2 : 470 ... 860 MHz
Voltage supply : 5 V
Bitrate : 4 ... 32

supply : 0.03 A
ulation : COFDM
ission mode : 2k/8k
ion range 1 : 174 ... 230 MHz
BRACKET
VESA wall mounting standards : VESA 400 x 400

SCOPE OF DELIVERY

MultyVision ISIO, Pedestal, Power cable, remote control TechniControl Plus incl. batteries, Remoty Plus, Multi audio/video adapter, Cleaning set, Instruction manual

