



## F Compression connector 4.9

Premium 4.9 F connector in compression design with shielding values of  $\geq 120$  dB

| EAN           | Colour | Item no.  |
|---------------|--------|-----------|
| 4019588100374 | silver | 0100/3337 |

### TOP FEATURES

High-end F connector  
100% waterproof

Operational up to 3 GHz  
Suitable for COAXSAT 120-4.6 and 140-4.6  
cables from TechniSat

Suitable for all RG6 coaxial cables 1.0/4.6  
Installation with compression pliers  
0000/3339 from TechniSat

### ATTENUATION

10 MHz : 0,01  
100 MHz : 0,01  
450 MHz : 0,01  
862 MHz : 0,01  
1000 MHz : 0,02  
2250 MHz : 0,02

Pack: 100 piece

### RETURN LOSS

65 - 470 MHz :  $\geq 38$  dB  
470 - 1800 MHz :  $\geq 38$  dB  
1800 - 2450MHz :  $\geq 35$  dB

### SHIELDING

30 - 1000 MHz :  $> 140$  dB CoMeT  
1000 - 2250 MHz :  $> 120$  dB CoMeT

### TECHNICAL DATA

Protection class : IPX8  
Impedance :  $75 \Omega$   
Diameter dielectric : max. 4,6 mm  
Diameter with coating : 6,8 ... 7 mm

### TRANSFER IMPEDANCE

5MHz :  $< 2,5$   
30 MHz :  $< 2,5$

### SCOPE OF DELIVERY