



2-way SAT tap 15 dB

Broadband 2-way tap, 15 dB

EAN	Item no.	Colour
4019588031319	0000/3131	silver

TOP FEATURES

Screening factor class A, EN 50083

diode decoupled

TECHNIROUTER-compatible

Broadband using from 5 to 2.400 MHz

DC path through on trunk

DECOUPLING

5 - 862 MHz : > 35 dB

950 - 1750 MHz : > 30 dB

1750 - 2150 MHz : > 28 dB

RETURN LOSS

5 - 862 MHz : > 10 dB

950 - 1750 MHz : > 10 dB

1750 - 2150 MHz : > 10 dB

TAP LOSS

5 - 862 MHz : 15 dB (± 1,5)

950 - 1750 MHz : 15 dB (± 2)

1750 - 2400 MHz : 15 dB (± 2,5)

TECHNICAL DATA

Input : 1

Outputs : 3 (1+2)

Frequency range : 5 ... 2400 MHz

Shielding factor : ≥ 75 dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75 Ω

TRANSMISSION LOSS

5 - 862 MHz : Typ. 2.5 dB

950 - 1750 MHz : Typ. 3.5 dB

1750 - 2400 MHz : Typ. 4.5 dB