



2 YEARS
WARRANTY

BESSER
MADE IN
GERMANY

ENERGY
SAVER
WITHOUT POWER SUPPLY

TECHNISWITCH 5/8 Mini

Compact multiswitch for distribution of 4 IF levels and terrestrial signals for 8 participants.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032606	blue/yellow	0000/3260	200 g	160 g	7.90 x 3.30 x 11.50 cm	9.50 x 4.00 x 12.20 cm

TOP FEATURES

Gain in satellite range

Slope fixed correction

For Quattro-LNB

Energy saving - usable without mains adapter

Input for terrestrial signals

Suitable for DOCSIS

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : -25 ... 45 °C

AMPLIFICATION

Sat : 2 ... 4 dB , bottom taps 3 ... 8 dB

Terrestrial : -15 dB

DECOUPLING

Output : > 30 dB

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 2 ... 790 MHz

TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Outputs : 8

Distribution length : max. 100 m

SCOPE OF DELIVERY

TECHNISWITCH 5/8 Mini, instruction manual