



## TECHNISWITCH 5/8 Mini

Compact multiswitch for distribution of 4 IF levels and terrestrial signals for 8 participants.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032606	blue/yellow	0000/3260	200 g	160 g	7.90 x 3.30 x 11.50 cm	9.50 x 4.00 x 12.20 cm

<b>AMBIENT OPERATING CONDITIONS</b> Humidity: 10 ... 75 % Ambient temperature: -25 ... 45 °C	Top features: Energy saving - usable without mains adapter Top features: Input for terrestrial signals Top features: Suitable for DOCSIS	<b>SCOPE OF DELIVERY</b> TECHNISWITCH 5/8 Mini, instruction manual
<b>AMPLIFICATION</b> Sat: 2 ... 4 dB , bottom taps 3 ... 8 dB Terrestrial: -15 dB	<b>RECEPTION RANGE</b> Sat: 950 ... 2150 MHz Terrestrial: 2 ... 790 MHz	
<b>DECOUPLING</b> Output: > 30 dB	<b>TECHNICAL DATA</b> Satellite inputs: 4 Terrestrial input: 1 Outputs: 8 Distribution length: max. 100 m	
<b>GENERAL CHARACTERISTICS</b> Top features: Gain in satellite range Top features: Slope fixed correction Top features: For Quattro-LNB		
<b>KEYFEATURES</b>		
HDTV	Multiple subscribers	
	1 orbit position	