



TECHNIPLUS ISIO 42

Full-HD ISIO smart TV with QuattroTuner Twin, Internet functionality and possibility of recording TV and radio programmes on an external storage medium. Ultra slim aluminium design.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588422117	silver/white	5542/9211	20 kg	15.5 kg	96.5 x 62.5 cm	106 x 70 x 17 cm

TOP FEATURES

Full-HD ISIO smart TV with QuattroTuner Twin for reception of digital satellite, digital cable and DVB-T without an extra receiver

First class design with close operation and aluminium base

IP module for access to the Internet, media libraries, online video libraries (VoD), apps and watchmi

UPnP/DLNA access via home network, remote access via MyTechniSat-App

Digital video recorder function via USB (DVRready) incl. Timeshift

2 CI+ interfaces

Persönliche TV-Kanäle und Themenkanäle von watchmi

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : 5 ... 35 °C

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2 / SCR1 = EN50494, SCR2 = EN50607

TECHNISAT ADDED VALUE SERVICES

SFI+ : Yes

TECHNIFAMILY : Yes

ISIPRO : Yes

AUTOINSTALL : Yes

TECHNIMATIC : Yes

INTERNET/NETWORK

ISIO Internet : Yes

ISIO live : Yes

HbbTV : Yes

VoD services : Ja

Webbrowser : Yes

Internet speed test : Yes

AUDIO

Speakers : 2 x 2-way sound system

AC3 Dolby Digital bitstream out : Yes

CONNECTIONS

HDMI (in) : 3

Digital electric audio output : Yes

Digital optical audio out : Yes

Audio out analogue (L,R) : Yes

Audio in/AUX in : Yes (3,5 mm Klinke)

Scart : 1 (über Adapter)

Ethernet 10/100 (RJ-45) : Yes

IEC-Connector : Yes

DECRYPTION SYSTEM

CI+ : Yes

DIMENSIONS / WEIGHT	HOTEL MODE	TUNER
Set depth without stand : 65 mm	Protected access to hotel mode : Yes	Tuner type : Doppel-QuattroTuner
Set width without stand : 965 mm	Customisable start screen : Yes	DVB-S tuner : 2
Set height without stand : 580 mm	Energy card function : Yes	DVB-C Tuner : 2
Weight without stand : 13 kg	USB cloning function : Yes	DVB-T Tuner : 2
DISPLAY	Multimedia connectors : Yes	Analogue UHF/VHF/CATV tuner : 2
Size (cm) : 107 cm	Lockable volume : Yes	Reception on : HDTV (MPEG-4), SD (MPEG-2)
Frequency : 400 Hz TechniMotion	Menu locking : Yes	Input impedance : 75 Ω
Format : 16:9	Control panel lock : Yes	TECHNISELECT 12 ready : Yes
Contrast ratio : 1200:1	Radio mode : Yes	TECHNIROUTER ready : Yes
Brightness : 350 cd/m ²	Alarm function : Yes	TUNER - ANALOGUE
Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Sleep timer : Yes	Reception range : 47 ... 862 MHz
Response time : < 8 ms	Mixing of channel slots : Yes	Video standards : PAL B/G, D/K, L/L, I
Angle of view : 178° / 178°	Multicode remote control : Yes	TUNER - CABLE
Picture and Picture (PAP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Selectable start source : Yes	Reception range : 47 ... 862 MHz
Freeze frame : Yes	Selectable start channel : Yes	Demodulation : 16-, 32-, 64-, 128-, 256-QAM
Zoom : Yes	MATERIALS CONTAINED	Symbol rate : 1.5 ... 7.2 Mbaud
SD : Yes	Lead : Yes	FEC : Reed-Solomon (204, 188)
720p : Yes	OTHER FEATURES	TUNER - SAT
1080i : Yes	OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	Reception range : 950 ... 2150 MHz
Type : Full-HD eLED	Total programme memory : 5000	DVB-S : QPSK
Size (inches) : 42	Regional channel selection : Yes	DVB-S : 2 ... 45 Mbaud (MCPC / SCPC)
Resolution (vertical and horizontal) : 1920 x 1080	POWER SUPPLY	DVB-S2 : 8PSK - QPSK
HD : Yes	Nominal voltage : 230 V	DVB-S2 : 10 ... 31 Mbaud (MCPC / SCPC)
HANDLING/COMFORT	Frequency : 50 Hz	FEC : RS, LDPC, BCH
CONNECT app : Yes	Mains adapter : internal	TUNER - TERRESTRIAL
Quick start : Yes	SUPPORTED FORMATS & CODECS	Reception range 1 : 174 ... 230 MHz
Parental Control : Ja	Video-Codecs : MPEG-2, MPEG-4, H.264, VC-1	Reception range 2 : 470 ... 862 MHz
Media Player : Yes	Video-Formats : MKV, MP4, MOV, MPG, TS, TS4, VOB, WMV, Xvid, M2TS, AVI, ASF	Demodulation : COFDM (QPSK, 16-QAM, 64-QAM)
Channel number mix : Yes	JPEG : Yes	Transmission mode : 2k/8k
Teletext : Yes	Audio-Formats : AAC, MP3, MP2, DDAC3, WMA	Bitrate : 4.98 ... 31.67 Mbit/s
Autostandby : Yes		FEC : 1/2, 2/3, 3/4, 5/6, 6/7, 7/8
Hotel mode : Yes		Voltage supply : 5 V
Sleep timer : Yes		Power supply : 0.03 A
Clock : Yes		WALL BRACKET
Alarm : Yes		VESA wall mounting standards : VESA 400 x 400
		SCOPE OF DELIVERY
		TECHNIPLUS ISIO, aluminium base, remote control (TECHNICONTROL with www key) incl. 2 AAA batteries, 2x3D glasses (42/47/55 inch), instruction manual incl. guarantee card

Testurteil(e) TECHNIPLUS ISIO 42



Testurteil: sehr gut
video (12/13)