



TECHNIROUTER 5/1x8 G-R

TECHNIROUTER base unit, suitable for the return path. It enables the connection of 4 IF levels (satellite blocks) and a terrestrial input for cable harness distribution for 8 participants

EAN	Colour	Item no.	Weight	Device (W x H x D)	Box
4019588132900	silber/gelb	0001/3290	340 g	14 x 11,5 x 3,2 cm	24,5 x 13,5 x 5,5 cm

TOP FEATURES

DiSEqC protocol according to EN 50494

1 orbit position without restrictions

Return path compatible

No new wiring required

Energy-saver - can be used without power supply

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 13 ... 18 dB

Terrestrial : -1 dB

DECOUPLING

Trunks : 45 dB

GENERAL CHARACTERISTICS

Top features : DiSEqC protocol according to EN 50494

Top features : 1 orbit position without restrictions

Top features : Return path compatible

Top features : No new wiring required

Top features : Energy-saver - can be used without power supply

POWER SUPPLY

Mains adapter : external DC 12V/0,46A (nur für LNB + Terrestrik)

Power consumption : 210 mA @13V (SCR-Ausgang, ohne LNB)

RECEPTION RANGE

Return path : 5 ... 65 MHz

Terrestrial : 65 ... 862 MHz

Sat : 950 ... 2.150 MHz

SINGLE-CABLE OUTPUT

Output frequency : 5 ... 2.150 MHz

Number of output channels : 8

Frequency of the output channels : 1284, 1400, 1516, 1632, 1748, 1864, 1980, 2096 MHz

Frequency SAT : 950 ... 2.150 MHz

Frequency DVB-T : 65 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Number of cable connections : 1

Subscribers per cable : maximal 8

TUNER

TECHNIROUTER ready : Yes

SCOPE OF DELIVERY

TECHNIROUTER5/1x8 G-R, user manual, power adapter

