



F Compression connector pack 4.9

4.9 First-class F compression male connector

| EAN | Item no. | Colour | Weight (Box) | Weight |
|---------------|-----------|--------|--------------|--------|
| 4019588103375 | 0010/3337 | silver | 6 g | 6 g |

TOP FEATURES

High-End F-Stecker
zu 100% Wasserdicht

Betriebsfähig bis 3 GHz
geeignet für 115dB und 120dB Kabel von TechniSat

geeignet für alle RG6-Koaxialkabel 1.0/4.6
Montage mit Kompressionszange 0000/3339 von TechniSat

ATTENUATION

10 MHz : 0.01 dB/100m

100 MHz : 0.01 dB/100m

450 MHz : 0.01 dB/100m

862 MHz : 0.01 dB/100m

1000 MHz : 0.02 dB/100m

2250 MHz : 0.02 dB/100m

RETURN LOSS

65 - 470 MHz : ≥ 38 dB

470 - 1800 MHz : ≥ 38 dB

1800 - 2450MHz : ≥ 35 dB

SHIELDING

30 - 1000 MHz : > 140 dB CoMeT

1000 - 2250 MHz : > 120 dB CoMeT

TECHNICAL DATA

Protection class : IPX8

Impedance : 75 Ω

Diameter dielectric : max. 4.6 mm

Diameter with coating : 6.8 bis 7 mm

TRANSFER IMPEDANCE

5MHz : < 2.5 m Ω /m

30 MHz : < 2.5 m Ω /m