



Base unit BS4 Professional

Cable head end Base unit for eight SkyCable cards

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588059603	white/blue	0000/5960	24,5 kg	22,1 kg	43,5 x 40 x 35 cm	55 x 53 x 44 cm

CONFIGURATION, MONITORING

Network interface : RJ45, Ethernet, 100BaseT, TCP/IP, SNMP

Service connection : RJ25, serial, for TechniNet Programmer

GENERAL

Power supply : 100 ... 250 VAC / 50 ... 60 Hz

Power input : Max. 250 W

Nominal temperature range : 0 ... 45 °C

Relative humidity : 0 ... 80 %

EMV : EN50083-2, EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003, EN61000-3-2:2006, EN61000-3-3:2008

Security : VDE 0855-1, DIN EN 60728-11:2005

POWER CONSUMPTION

Power switch : Yes

POWER SUPPLY

Nominal voltage : 230 V

Mains adapter : internal

Frequency : 50 ... 60 Hz

RF OUTPUT

Reception range : 42 ... 862 MHz

input / output : F-socket

Impedance : 75 Ω

Output level : ≤ 107 (± 3 dB) @ 256-QAM typisch

SAT IF INPUT / MULTISWITCH

Reception range : 950 ... 2.150 MHz

input / output : F-socket

Impedance : 75 Ω

Input level : 50 ... 90 (Summenpegel)

LNB voltage supply : 13 / 18 V & 22kHz

LNB power supply : Max. 300 mA je Eingang

SCOPE OF DELIVERY

TechniNet BS4 Professional base unit, Multi Wall Mount + 19 "rack, power cord, installation manual