



## TECHNISYSTEM 5/8 G2

Multi-switch system with connection possibility of 4 ZF levels for distribution to up to 8 participants

| EAN           | Colour      | Item no.  | Weight (Box) | Weight | Device (W x H x D)   | Box                   |
|---------------|-------------|-----------|--------------|--------|----------------------|-----------------------|
| 4019588132498 | blue/yellow | 0001/3249 | 1 kg         | 300 g  | 17,2 x 11,5 x 3,2 cm | 17,4 x 13,5 x 10,5 cm |

### TOP FEATURES

Professionelles Multischaltersystem für Großanlagen

Ohne Dämpfung im Sat-Bereich

Mit Schräglagenentzerrung

Für Quattro-LNB

### AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

### AMPLIFICATION

Sat : -2 ... 3 dB

Terrestrial : -4 ... -1 dB

### DECOUPLING

Output : > 35 dB

Trunks : 40 dB

### GENERAL CHARACTERISTICS

Top features : Professionelles Multischaltersystem für Großanlagen

Top features : Ohne Dämpfung im Sat-Bereich

Top features : Mit Schräglagenentzerrung

Top features : Für Quattro-LNB

### POWER CONSUMPTION

Power switch : Nein

### POWER SUPPLY

Mains adapter : extern DC 15V/1,2A

Nominal voltage : 100 ... 240 V

Frequency : 50 ... 60 Hz

### RECEPTION RANGE

Sat : 950 ... 2.150 MHz

Terrestrial : 47 ... 862 MHz

### TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Outputs : 8

Distribution length : 100 m

### SCOPE OF DELIVERY

TECHNISYSTEM 5/8 G2, Power supply, Manual