



TECHNILINE 32 HD

32 inch Full-HD digital TV with integrated HDTV Multi Tuner for reception of analogue and digital TV including HDTV

EAN	Item no.	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box	Weight without stand
4019588532069	5532/0306	black/silver metallic	17,5 kg	13,5 kg	780 x 530 x 95 mm	78 x 58,5 x 20 cm	88,5 x 67,3 x 26 cm	
4019588523166	5532/0316	black/titanium metallic	17,5 kg	13,5 kg	780 x 530 x 95 mm	78 x 58,5 x 20 cm	88,5 x 67,3 x 26 cm	
4019588532267	5532/0326	black/black	17,5 kg	13,5 kg	780 x 530 x 95 mm	78 x 58,5 x 20 cm	88,5 x 67,3 x 26 cm	
4019588325104	5532/1306	silver	17 kg	13,5 kg	780 x 530 x 95 mm	78 x 58,5 x 20 cm	88,5 x 67,3 x 26 cm	13 kg
4019588325111	5532/1316	titanium	17 kg	13,5 kg	780 x 530 x 95 mm	78 x 58,5 x 20 cm	88,5 x 67,3 x 26 cm	13 kg

TOP FEATURES

HDTV- Multituner for HDTV and SDTV:
DVB-S2, DVB-C, DVB-T, analogue TV
(terrestrial and cable), analogue radio FM
(UKW)

Integrated loudspeaker system

2x Common Interface +

2 HDMI-connections (HDCP implemented)

Resolution (lines x rows) 1920x1080

Number of colours: 16,7 millions

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 ... 35 °C

Humidity : 10 ... 75 %

LNB CONTROL

Current consumption : 400 mA

DiSEqC : DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat
Channel Router

Horizontal : <20 V without load, > 17.2 V at
400 mA / LNB shut-off standby mode V

Band switch : 22 kHz

Vertical : <14 V without load, > 11.5 V at
400 mA V

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

AUDIO

Speakers : 2 x 2-way sound system with bass
reflex

CONNECTIONS	HANDLING/COMFORT	SUPPORTED FORMATS & CODECS
HDMI™ (in) : 2	Sleep timer : Yes	Video-Codecs : MPEG-1, MPEG-2, H.264
Digital electric audio output (S/PDIF) : Yes (Cinch)	Clock : Yes	Video-Formats : TS, MPG, TS4, VOB
Digital optical audio out : Yes (Toslink)	Alarm : Yes	JPEG : Yes
Digital audio in (S/PDIF) : Yes (Cinch)	HOTEL MODE	Audio-Formats : MP2, MP3
Audio in/AUX in : Yes (3.5mm Klinke)	Customisable start screen : Yes	TUNER
VGA : Yes	Configurable on times : Yes	Tuner type : Single-HDTV-Multituner
YUV (component input) : Yes	Energy card function : Yes	DVB-S tuner : 1
Scart : 1	USB cloning function : Yes	DVB-C Tuner : 1
F socket : 1	Multimedia connectors : Yes	DVB-T Tuner : 1
IEC-Connector : Yes	Menu locking : Yes	Analogue UHF/VHF/CATV tuner : 1
DECRYPTION SYSTEM	Radio mode : Yes	Input impedance : 75 Ω
CI+ : Yes	Mixing of channel slots : Yes	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
DIMENSIONS / WEIGHT	Multicode remote control : Yes	TECHNIROUTER ready : Yes
Set height without stand : 530 mm	Fireproofed housing : Yes	TUNER - ANALOGUE
Set depth without stand : 95 mm	MATERIALS CONTAINED	Video standards : B/G stereo, D/K mono, L/L, I, NICAM
Set width without stand : 780 mm	Lead : Yes	Reception range : 46 860 MHz
Weight without stand : 11,5 kg	OTHER FEATURES	TUNER - CABLE
DISPLAY	OSD languages : English, Dutch, French, Russian, Hungarian, German, Spanish, Greek, Swedish, Polish, Turkish, Italian, Portuguese, Czech	Symbol rate : 1,7 7
Size (cm) : 81 cm	Total programme memory : 5.000	Reception range : 51 858 MHz
Format : 16:9	Regional channel selection : Yes	FEC : Reed-Solomon
Contrast ratio : 4.000:1	POWER CONSUMPTION	Demodulation : 16/32/64/128/256 QAM
Picture in Picture (PIP) : Yes externe Quelle	SFIplus updating : 25 W	TUNER - SAT
Brightness : 450 cd/m²	Energy class : C	DVB-S : 2 ... 45
Response time : < 8 ms	Software update : 25 W	Reception range : 950 ... 2.150 MHz
Angle of view : 178	Standby fast start : 21 W	Viterbi rates : 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 7/8, 8/9, 9/10 Autoanpassung
Picture and Picture (PAP) : Yes externe Quelle	Standby LED : 0,72 W	DVB-S2 : 10 ... 31
Freeze frame : Yes	In operation : 80 W	DVB-S2 : 8PSK - QPSK
Zoom : Yes	annual energy consumption when switched on : 117 kilowatt hour per annum	FEC : Viterbi and Reed-Solomon
Type : TFT-LCD "Full HD"	Standby : 0,5 W	DVB-S : QPSK
720p : Yes	Off status : 0 W	TUNER - TERRESTRIAL
Size (inches) : 32	Power switch : Yes	Reception range 1 : 174 ... 230 MHz
SD : Yes	POWER SUPPLY	Demodulation : COFDM
HD : Yes	Frequency : 50 Hz	Power supply : 0,03 A
1080i : Yes	Mains adapter : internal	Bitrate : 4 32
Resolution (vertical and horizontal) : 1920 x 1080	Nominal voltage : 230 V	Voltage supply : 5 V
GENERAL CHARACTERISTICS		Transmission mode : 2k/8k
Appearance : TFT-LCD Full HD		Reception range 2 : 470 ... 860 MHz
		WALL BRACKET
		VESA wall mounting standards : VESA 400 x 200
		SCOPE OF DELIVERY
		TechniLine 32 HD, Pedestal, 230 V euro connection cable, Remote control with batteries, Angle adapter USB, Angle adapter jack plug, Hexagon tool, Maintenance instruction with maintenance set, Instruction manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.