



DIGIT ISIO C

HDTV cable receiver with Twin-Tuner, Internet access and DVR functionality via USB for the record of TV- and radio channels to an external HDD

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588147737	0001/4773	silver	2,9 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm
4019588047730	0000/4773	black	2,9 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm

TOP FEATURES

DigitalKabel-Receiver mit HDTV-Twin-Tuner

ISIO Internet-Technologie: Zugriff auf das Internet, Mediatheken, Online-Videotheken (VoD), HbbTV, Apps und ISIO-Browsing

Digitale Videorekorder-Funktion via USB (DVRready) inkl. Timeshift sowie paralleles Aufzeichnen von zwei verschiedenen Programmen

Conax Entschlüsselung mit Chipset-Pairing und 2 CI+ Schnittstellen (kompatibel zu Kabel Deutschland, Unitymedia, Sky und anderen CI+ Modulen)

UPnP/DLNA/Client- & Serverfunktion für Heimvernetzung, Fernzugriff über MyTechniSat-App

Kompatibel zu watchmi

SONSTIGES

ts_mehrwert_isipro_kabel : Yes

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 ... 35 °C

Humidity : 10 ... 75 %

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HTML 5 support : Yes

HbbTV : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

eSATA : Yes

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes (rechts / links)

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

DECRYPTION SYSTEM

Conax : Yes

Conax CSP : Yes Ab Software 2.49.0.7-2165k

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

SD : Yes

576p : Yes

HD : Yes

576i : Yes

1080i : Yes

720p : Yes

HANDLING/COMFORT

Clock : Yes

Sleep timer : Yes

Alarm : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

OTHER FEATURES	POWER SUPPLY	SUPPORTED FORMATS & CODECS
OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Swedish, Russian, Spanish, Czech, Turkish, Hungarian	Mains adapter : internal	Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX
Total programme memory : 5.000	Nominal voltage : 230 V	Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI
Loophrough : Yes	Frequency : 50 Hz	JPEG : Yes
POWER CONSUMPTION	READY FOR RECEPTION	TECHNISAT CONNECT
Standby fast start : 7,75 W	M7 : Yes	Control : Yes
Standby LED : 0,16 W		SFI : Yes
In operation : 10,1 W		TUNER
		Tuner type : DigitalCable
		DVB-C Tuner : 2
		Reception on : HDTV (MPEG-4), SD (MPEG-2)
		TUNER - CABLE
		Reception range : 47 ... 862 MHz
		Demodulation : 16 / 32 / 64 / 128 / 256 QAM
		Symbol rate : 1,5 ... 7,2
		FEC : Reed-Solomon (204, 188)



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.