



MultyVision 40

Full-HD eLED Digital Television with Dual HDTV multituner for reception of analogue and digital TV. Integrated DVR for recording HD and standard TV and radio programmes.

EAN	Weight without stand	Item no.	Hard drive	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
401958874 0068	17 kg	5740/0306	500 GigaByte	silver	28 kg	20 kg	955 x 638 x 61 mm	95,5 x 69,2 x 22 cm	113 x 92 x 30 cm
401958874 0167	17 kg	5740/0316	500 GigaByte	titanium	28 kg	20 kg	955 x 638 x 61 mm	95,5 x 69,2 x 22 cm	113 x 92 x 30 cm

TOP FEATURES

Dual HDTV multituner for receiving DVB-S, DTT and DVB-C incl. HDTV

Integrated DVR (500 GB hard drive) and recording

Rotating pedestal

LED time and program display

2x Common Interface (CI+)

UPnP (Universal Plug and Play), incl. DLNA

AMBIENT OPERATING CONDITIONS

Humidity : 10 - 75 %

Ambient temperature : 5 - 35 °C

LNB CONTROL

Band switch : 22 kHz

Horizontal : <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V

Vertical : <14 V without load, > 11.5 V at 400 mA V

Current consumption : 400 mA max. kurzschlussfest 400 mA

DiSEqC : DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

AUDIO

AC3 Dolby Digital bitstream out : Yes

Speakers : 2 x broadband speakers with bass reflex

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (in) : 3 (davon 1 x HDMI Mini Front)

HDMI™ (out) : 1

Smartcard reader : Yes (Conax)

Digital electric audio output (S/PDIF) : Yes (Adapter)

Digital optical audio out : Yes (Toslink)

Digital audio in (S/PDIF) : Yes (Adapter)

Audio out analogue (RCA) : Yes (3.5mm Klinke)

AV input : Yes (Front)

Audio in/AUX in : Yes (3.5mm Klinke)

VGA : Yes

YUV (component input) : Yes (Adapter)

Scart : 1

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

F socket : 2

IEC-Connector : Yes

DECRYPTION SYSTEM	HOTEL MODE	SUPPORTED FORMATS & CODECS
Conax : Yes	Customisable start screen : Yes	Video-Codecs : MPEG-1, MPEG-2, H.264
CI+ : Yes	Configurable on times : Yes	Video-Formats : TS, MPG, TS4, VOB
DIMENSIONS / WEIGHT	Energy card function : Yes	JPEG : Yes
Set width without stand : 955 mm	USB cloning function : Yes	Audio-Formats : MP2, MP3
Weight without stand : 17 kg	Multimedia connectors : Yes	TUNER
Set depth without stand : 61 mm	Menu locking : Yes	DVB-S tuner : 2
Set height without stand : 638 mm	Integrated LED clock : Yes	DVB-C Tuner : 2
DISPLAY	Radio mode : Yes	DVB-T Tuner : 2
Size (cm) : 102 cm	Mixing of channel slots : Yes	Analogue UHF/VHF/CATV tuner : 2
Frequency : 200 Hz	Multicode remote control : Yes	TECHNIROUTER ready : Yes
Format : 16:9	Fireproofed housing : Yes	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
Contrast ratio : 5.000:1	MATERIALS CONTAINED	Input impedance : 75 Ω
Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Lead : Yes	TUNER - ANALOGUE
Brightness : 450 cd/m²	OTHER FEATURES	Video standards : B/G stereo, D/K mono, L/L, I
Response time : 6 ms	OSD languages : Hungarian, Greek, Russian, Spanish, Italian, Polish, Portuguese, Swedish, Turkish, German, English, Dutch, French, Czech	Reception range : 47 ... 862 MHz
Angle of view : 178° / 178°	Total programme memory : 5.000	TUNER - CABLE
Picture and Picture (PAP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Regional channel selection : Yes	FEC : Reed-Solomon
Freeze frame : Yes	POWER CONSUMPTION	Reception range : 51 ... 858 MHz
Zoom : Yes	SFIplus updating : 31 W	Demodulation : 16 / 32 / 64 / 128 / 256 QAM
HD : Yes	Energy class : B	Symbol rate : 1,7 ... 7
Size (inches) : 40	Software update : 31 W	TUNER - SAT
Resolution (vertical and horizontal) : 1920 x 1080	Standby fast start : 24 W	DVB-S2 : QPSK - 8PSK
SD : Yes	Standby LED : 0,46 W	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
1080i : Yes	In operation : 94 W	DVB-S2 : 10 ... 31
Type : Edge LED LCD	annual energy consumption when switched on : 130 kilowatt hour per annum	DVB-S : 1 ... 45
720p : Yes	Off status : 0 W	FEC : Viterbi and Reed-Solomon
GENERAL CHARACTERISTICS	Power switch : Yes	DVB-S : QPSK
Hard drive : 500 GigaByte	Contains no mercury : Yes	Reception range : 950 ... 2.150 MHz
Appearance : Slim 55mm	POWER SUPPLY	TUNER - TERRESTRIAL
HANDLING/COMFORT	Nominal voltage : 230 V	Bitrate : 4 ... 32
Alarm : Yes	Mains adapter : internal	Power supply : 0,03 A
Clock : Yes	Frequency : 50 Hz	Voltage supply : 5 V
Sleep timer : Yes		Transmission mode : 2k/8k
		Demodulation : COFDM
		Reception range 2 : 470 ... 860 MHz
		Reception range 1 : 174 ... 230 MHz
		WALL BRACKET
		VESA wall mounting standards : VESA 400 x 400
		SCOPE OF DELIVERY
		MultiVision, Pedestal, Power cable, remote control TechniControl Plus incl. batteries, Remoty Plus, Multi audio/video adapter, Cleaning set, Instruction manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.