



TECHNIROUTER MINI 2/1x2

Expand an existing cable derivation into a Twin solution or into a two-subscriber solution without laying additional cables

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032897	silver/yellow	0000/3289	400 g	200 g	5 x 2,8 x 11,5 cm	18 x 4 x 18,5 cm

TOP FEATURES

Expansion of coaxial line to twin function
No additional cable routing required

2 adjustable orbit positions
Very compact dimensions

Can be connected behind Twin, Quatro Switch LNB and multiswitch
Terrestrial outlet for DVB-T(2)/UHV

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %
Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 2 dB
Terrestrial : -3 dB

DECOUPLING

Trunks : 30 dB

GENERAL CHARACTERISTICS

Top features : Expansion of coaxial line to twin function
Top features : No additional cable routing required
Top features : 2 adjustable orbit positions
Top features : Very compact dimensions
Top features : Can be connected behind Twin, Quatro Switch LNB and multiswitch
Top features : Terrestrial outlet for DVB-T(2)/UHV

POWER CONSUMPTION

In operation : max. 2 W (Standby 0 W)

POWER SUPPLY

Nominal voltage : 230 V
Frequency : 50 Hz
Mains adapter : extenal 12 VDC/1,5 A

RECEPTION RANGE

Sat : 950 ... 2.150 MHz
Terrestrial : 47 ... 862 MHz

SINGLE-CABLE OUTPUT

Output frequency : 47 ... 2.150 MHz
Number of output channels : 2
Frequency of the output channels : 1284, 1400 MHz
Frequency SAT : 1.250 ... 1.430 MHz
Frequency DVB-T : 47 ... 862 MHz
Output level : - 3 dB

TECHNICAL DATA

Satellite inputs : 2
Number of cable connections : 1
Subscribers per cable : 2

SCOPE OF DELIVERY

TechniRouter Mini 2/1x2, Manual