



DIGIT ISIO S

HDTV satellite receiver with Twin-Tuner, Internet access and DVR functionality via USB for the record of TV and radio channels to an external HDD

EAN	Colour	Item no.	Hard drive	Weight (Box)	Weight	Device (W x H x D)	Box
4019588647534	black	0006/4753	extern	2,6 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm

TOP FEATURES

HDTV-Twin-Tuner

Digital video recorder via USB (DVRready)

IP module for access to media libraries and video on demand services

Free browsing, HbbTV (if provided by your broadcaster) and ISIO Live! (TechniSat Service Portal)

2 Common Interface CI+

UPnP / DLNA / Client- & server function for home networking

Unterstützt Audio Codierformat AAC

MULTIMEDIA

DVR function : USB

Timeshift : Yes

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 ... 35 °C

Humidity : 10 ... 75 %

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

ISIPRO : Yes

AUTOINSTALL : Yes

TECHNIMATIC : Yes

SFI : Yes

TECHNIFAMILY : Yes

INTERNET/NETWORK

ISIO Internet : Yes

Webbrowser : Yes

HTML 5 support : Yes

Internet speed test : Yes

ISIO live : Yes

HbbTV : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

USB : 3 (USB 2.0)

eSATA : Yes

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes (rechts / links)

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes

F socket : 2

DECRYPTION SYSTEM

Conax : Yes

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

SD : Yes

HD : Yes

1080i : Yes

720p : Yes

HANDLING/COMFORT

Media Player : Yes

Alarm : Yes

Sleep timer : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

OTHER FEATURES	SUPPORTED FORMATS & CODECS	TUNER
OSD languages : German, Bulgarian, English, French, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Slovakian, Swedish, Spanish, Czech	Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX	Tuner type : DigitalSat
Total programme memory : 5.000	Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI	DVB-S tuner : 2
POWER CONSUMPTION	JPEG : Yes	Single Cable Solution (SatCR) : SCR1 = EN50494
Standby fast start : 6,5 W	Audio-Formats : AAC, MP3, M4A, MP2	Reception on : HDTV (MPEG-4 & 2), SD (MPEG-2)
Standby LED : < 0,2 W	TECHNISAT CONNECT	TECHNISELECT 12 ready : Yes
In operation : 11,05 W	Control : Yes	TECHNIROUTER ready : Yes
POWER SUPPLY	SFI : Yes	TUNER - SAT
Nominal voltage : 230 V		Reception range : 950 ... 2.150 MHz
Frequency : 50 Hz		Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
Mains adapter : internal		DVB-S : QPSK
		DVB-S : 2 ... 45
		DVB-S2 : 8PSK-QPSK
		DVB-S2 : 10 ... 31
		FEC : Viterbi and Reed-Solomon
		SCOPE OF DELIVERY
		DIGIT ISIO S INTERNATIONAL EDITION, Remote Control TECHNICONROL with batteries, Power Cable, HDMI Cable, Instruction Manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.