



## TechniPro RV 600-13

Sat-transfer socket with 13 dB insertion loss for loop through-systems in one cable solutions for flush mounting with frame and cover

| EAN           | Colour | Item no.  | Weight (Box) | Weight | Device (W x H x D) | Box          |
|---------------|--------|-----------|--------------|--------|--------------------|--------------|
| 4019588031814 | white  | 0000/3181 | 200 g        | 100 g  | 7,8 x 7,8 x 4 cm   | 8 x 8 x 5 cm |

### CONNECTOR TYPE

Radio : IEC connector (f)

TV : IEC connector (m)

SAT : F-socket

### FREQUENCY RANGE

Radio : 5 ... 139 MHz

SAT : 950 ... 2.150 MHz

TV : 5 ... 860 MHz

### SHIELDING FACTOR

47 - 300 MHz : 75 dB

300 - 470 MHz : 75 dB

470 - 950 MHz : 65 dB

950 - 2150 MHz : 55 dB

### TAP LOSS

Radio : typ. 18 dB

SAT : typ. 13 dB

TV : typ. 15 dB

### TRANSMISSION LOSS

VHF : 1,8 dB

UHF : 2,3 dB

Sat : typ. 3,3 dB

### SCOPE OF DELIVERY

TechniPro RV 600-13, housing for surface mounting, cover