



MULTYTENNE DUOSAT

Receiving oft two satellitte positions with only 45 cm of antenna diameter, without the antenna having to be rotated.

EAN	Item no.
4019588048126	1045/8812
4019588348127	1345/8812
4019588448124	1445/8812
4019588758827	1745/8812
4019588548121	1545/8812
4019588048836	1045/8813
4019588348837	1345/8813
4019588448834	1445/8813
4019588748835	1745/8813
4019588548138	1545/8813

TOP FEATURES

1 or 2 participants

2 orbital positions (Eutelsat 13° East & Astra 19,2° East)

perfect for ground- or wall mounting

LOCAL OSCILLATOR

Low band : 9,75 GHz $\pm$ 3MHz

High band : 10,6 GHz $\pm$ 3MHz

LNB CONTROL

Vertical : 11 ... 14 V

Horizontal : 16 ... 20 V

Band switch : 22 kHz

DiSEqC : 1

AMBIENT OPERATING CONDITIONS

Humidity : 5 ... 100 %

Ambient temperature : -40 ... 65 °C

GENERAL CHARACTERISTICS

Top features : 1 or 2 participants

Material : Aluminium

Top features : 2 orbital positions (Eutelsat 13° East & Astra 19,2° East)

Top features : perfect for ground- or wall mounting

Material strength : 1 mm

Coating : Powder-coated on both sites

INPUT FREQUENCY RANGE

Low band : 10,7 - 11,7 GHz

High band : 11,7 - 12,75 GHz

NOISE FACTOR

Lower frequency range : 0,7 dB max.

Upper frequency range : 0,8 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 - 1.950 MHz

High band : 1.100 - 2.150 MHz

POWER SUPPLY	TECHNICAL DATA	SCOPE OF DELIVERY
LNB voltage supply : 11 ... 20 V	F/D : 0,6	Satellite dish antenna SATMAN
Power consumption : 170 mA (Typ.)	Offset angle : 30 °	45,Multyenne DuoSatreception unit
	Gain : 32,2 dBi @11,3 GHz	(LNBS), wall mount, installation instructions
	Satellite positions : Eutelsat 13° East, Astra 19,2° East	
	Feed reception : forMULTYTENNE DUOSAT LNB	

COAXSAT 2150 Set 10 m + 2 F-Stecker

ARTICLE INFORMATION	Item no. : 0001/3610
EAN : 4019588136106	Weight (Box) : 388 g
Colour : white	Weight : 388 g

black/white