




TECHNITOP HAV 25

CATV amplifier with 25 dB gain and active return path

EAN	Item no.
4019588056251	0000/5625

TOP FEATURES

25 dB amplification

active return path for internet and phone (DOCSIS)

alu-diecast housing

adjustable attenuation and equalization

developed according to KDG1-
classification TS 140

shielding class A according to EN 500083-2

GENERAL CHARACTERISTICS

Top features : 25 dB amplification

Top features : active return path for
internet and phone (DOCSIS)

Top features : alu-diecast housing

Top features : adjustable attenuation and
equalization

Top features : developed according to
KDG1- classification TS 140

Top features : shielding class A according to
EN 500083-2

OUTPUT LEVEL

IMA DIN 45004B VHF : 98 dB

IMA DIN 45004B UHF : 98 dB

POWER CONSUMPTION

Power switch : Nein

POWER REQUIREMENT

Power input : 6 W

POWER SUPPLY

Mains adapter : internal

Nominal voltage : 230 V ~

Frequency : 50 Hz

RANGE OF ADJUSTMENT

Attenuator : 20 dB

Equaliser : 18 dB

TECHNICAL DATA

Frequency range : 85 ... 1.006 MHz

Frequency range return path : 5 ... 65 MHz

Amplification : 22 ... 25 dB

CSO / CTB : 98

Noise factor : ≤ 7 dB

Shielding factor : ≥ 80 dB EN 50083-2
(Klasse A)

Protection class : IP 40

Connector type : F female

Impedance : 75 Ω

Return loss : ≥ 14 dB (-1,5 dB/Okt.)

Interstage attenuator : 6 dB

SCOPE OF DELIVERY

TECHNITOP HAV 25, manual