



TECHNILINE PRO 32 SL

Full HD Smart TV with single cable TwinTuner, DELUXE SOUND 2.1 and extensive Internet and networking features

EAN	Colour	Item no.
4019588563278	black/titanium metallic	5632/9716

TOP FEATURES

Einkabel-TwinTuner zum Empfang von DVB-S/S2, DVB-C und DVB-T2 (H.265/HEVC)

TechniSat DELUXE SOUND 2.1 powered by ELAC (integrierte Soundbar und externer Subwoofer)

DVRready zum Aufzeichnen auf USB-Datenträger oder Netzwerkspeicher (NAS)

Timeshift (i.V.m. einem Speichermedium)

CI+ Schnittstelle für Pay-TV

ISIO-Internet: Zugriff auf Mediatheken, ISIO-Apps und HbbTV

Internet-Themenkanäle von watchmi

Multimedia-Streaming im Heimnetzwerk (über UPnP)

Steuerung per CONNECT-App (iOS/Android)

TECHNISAT ADDED VALUE SERVICES

SFI+ : Yes

ISI-Mode : Yes

TECHNIFAMILY : Yes

ISIPRO : Yes

AUTOINSTALL : Yes

TECHNIMATIC : Yes

MULTIMEDIA

DVR function : Ja

DVR storage medium : USB, NAS

Timeshift : Yes

Recordings edition function : Yes

Recordings folder management : Yes

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : 5 ... 35 °C

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2 / SCR1 = EN50494, SCR2 = EN50607

INTERNET/NETWORK

Internet : Yes

ISIO Internet : Yes

ISIO live : Yes

HbbTV : Yes

VoD services : Ja

Webbrowser : Yes

HTML 5 support : Yes

Internet speed test : Yes

AUDIO

HDMI ARC : Yes

Speakers : 2 x 2-way sound system

CONNECTIONS	HANDLING/COMFORT	POWER SUPPLY
HDMI™ (in) : 2	CONNECT app : Yes	Nominal voltage : 230 V
USB : 2 (USB 2.0)	Electronic Program Guide (EPG) : Ja	Frequency : 50 Hz
Common Interface Plus (CI+) : Yes	Quick start : Yes	Mains adapter : internal
Digital electric audio output (S/PDIF) : Yes	Parental Control : Ja	STREAMING
Audio out analogue (RCA) : Yes (3,5 mm Klinke)	Media Player : Yes	DLNA Server : Yes
Audio / video input analog (3.5 mm jack) : 1	Channel number mix : Yes	DLNA Client : Yes
Ethernet 10/100 (RJ-45) : Yes	Teletext : Yes	Cloud store : Ja
F socket : 1	Alarm : Yes	Parental Control : Yes
IEC-Connector : Yes	Autostandby : Yes	TechniCast : Ja (optional über Dongle)
Headphone output : Yes (3,5 mm Klinke)	Sleep timer : Yes	SUPPORTED FORMATS & CODECS
DECRYPTION SYSTEM	Hotel mode : Yes	Video-Codecs : MPEG-2, MPEG-4, H.264 (bis H.264/AVC Level 4.2), H.265, DivX (MPEG4 part2), VC-1
CI+ : Yes	Clock : Yes	Video-Formats : M4V, MP4, MKV, MOV, MPG, TS, TS4, VOB, WMV, M2TS, AVI, ASF
DIMENSIONS / WEIGHT	HOTEL MODE	Picture-Formats : BMP, JPEG, GIF, PNG, TIFF
Stand width : 385 mm	Protected access to hotel mode : Yes	Audio-Formats : WAV, MP3, AAC, FLAC, M4A, MP2, OGG, DDAC3, AIFF, WMA
Weight without stand : 9,2 kg	Customisable start screen : Yes	TECHNISAT CONNECT
Stand height : 30 mm	Energy card function : Yes	Control : Yes
Stand depth : 185 mm	USB cloning function : Yes	SFI : Yes
DISPLAY	Multimedia connectors : Yes	TUNER
Type : FullHD eLED	Lockable volume : Yes	Tuner type : Einkabel-TwinTuner
Resolution (vertical and horizontal) : 1920 x 1080	Menu locking : Yes	Twin-Tuner : Yes Einkabel-TwinTuner
Size (cm) : 80 cm	Control panel lock : Yes	DVB-S tuner : 2
Size (inches) : 32	Radio mode : Yes	Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607
SD : Yes	Alarm function : Yes	DVB-C Tuner : 2
HD : Yes	Sleep timer : Yes	Tuner DVB-T2 : 2
1080p : Yes	Mixing of channel slots : Yes	DVB-T Tuner : 2
1080i : Yes	Multicode remote control : Yes	Analogue UHF/VHF/CATV tuner : 1
720p : Yes	Selectable start source : Yes	Reception on : HDTV (MPEG-4), SD (MPEG-2)
576p : Yes	Selectable start channel : Yes	Input impedance : 75 Ω
576i : Yes	MATERIALS CONTAINED	TECHNISELECT 12 ready : Yes
480p : Yes	Lead : Yes	TECHNIROUTER ready : Yes
480i : Yes	OTHER FEATURES	TUNER - ANALOGUE
Format : 16:9	OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	Reception range : 47 ... 862 MHz
Zoom : Yes	Regional channel selection : Yes	Video standards : PAL B/G, D/K, L/L, I
Freeze frame : Yes	POWER CONSUMPTION	TUNER - CABLE
GENERAL CHARACTERISTICS	Energy class : A	Reception range : 47 ... 862 MHz
Appearance : Slim 55mm	In operation : 38 W	Demodulation : 16-, 32-, 64-, 128-, 256-QAM
	annual energy consumption when switched on : 55 kilowatt hour per annum	Symbol rate : 1,5 ... 7,2
	Standby : 0,5 W	FEC : Reed-Solomon (204, 188)
	Off status : 0 W	TUNER - SAT
	Power switch : Yes	Reception range : 950 ... 2.150 MHz
	Contains no mercury : Yes	DVB-S : QPSK
		DVB-S : 2 ... 45 (MCPC / SCPC)
		DVB-S2 : 8PSK - QPSK
		DVB-S2 : 10 ... 31 (MCPC / SCPC)
		FEC : RS, LDPC, BCH

TUNER - TERRESTRIAL

Reception range 1 : 174 ... 230 MHz

Reception range 2 : 470 ... 862 MHz

Demodulation : COFDM (QPSK, 16-QAM, 64-QAM)

Transmission mode : 2k/8k

Bitrate : 4,98 ... 31,67

FEC : 1/2, 2/3, 3/4, 5/6, 6/7, 7/8

Voltage supply : 5 V

Power supply : 0,03 A

WALL BRACKET

VESA wall mounting standards : VESA 200 x 100



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.