




DIGIDISH 45 + 1 x DIGIT S3 HD

EAN	Colour	Item no.
4019588847125	beige	8614/4712
4019588947122	slate/grey	9614/4712
4019588647121	brick/red	6614/4712
4019588747128	polar/white	7614/4712
4019588547124	yellow with Smiley	5614/4712

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

HANDLING/COMFORT

Ideal for camping : Yes

DIGIT S3 HD

ARTICLE INFORMATION	ISIPRO : Yes	720p : Yes
EAN : 4019588047129	ISI-Mode : Yes	576p : Yes
Item no. : 0000/4712	SFI : Yes	576i : Yes
Colour : black	AUTOINSTALL : Yes	
Weight (Box) : 1,03 kg	INTERNET/NETWORK	
Weight : 380 g	Internet speed test : Yes	
Device (W x H x D) : 18 x 4,4 x 13 cm	CONNECTIONS	
Box : 26 x 8 x 17 cm	HDMI™ (out) : 1	
AMBIENT OPERATING CONDITIONS	USB : 1 (USB 2.0)	
Ambient temperature : 5 ... 35 °C	Digital electric audio output (S/PDIF) : Yes	
Humidity : 10 ... 75 %	audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)	
LNB CONTROL	Ethernet 10/100 (RJ-45) : Yes	
Vertical : 14 V	F socket : 1	
Horizontal : 18 V	DISPLAY	
Band switch : 22 kHz	SD : Yes	
Current consumption : max. 400 mA (kurzschlussfest)	HD : Yes	
DiSEqC : 1.0 / 1.2	1080p : Yes	
TECHNISAT ADDED VALUE SERVICES	1080i : Yes	
TECHNIFAMILY : Yes		

HANDLING/COMFORT
Page memory : 1.000
Teletext subtitles : Yes
Media Player : Yes
Parental Control : Ja
Teletext : Yes
Channel presets : 4.999
Sleep timer : Yes
Quick start : Yes
Autostandby : Yes
Remote control : Yes
Selection regional channels : Yes
NETWORK & COMMUNICATION
100Base-T : Yes
IPv4 : Yes
TCP/IP : Yes
OTHER FEATURES

OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian
Total programme memory : 4.999
POWER CONSUMPTION
Standby LED : 0,3 W
In operation : 6,3 W
POWER SUPPLY
Nominal voltage : 230 V
Frequency : 50 Hz
Mains adapter : external DC 12V/2A
SUPPORTED FORMATS & CODECS
Video-Codecs : MPEG-2, MPEG-4, H.264
Video-Formats : MTS, MPG, TS, TS4, M2TS, AVI, ASF
Picture-Formats : BMP, JPEG, GIF, PNG, TIFF
Audio-Formats : WAV, MP3, M4A, MP2, DDAC3
TUNER
Tuner type : DigitalSat

DVB-S tuner : 1
Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607
Satellite radio : Yes
Internet radio : Yes
Reception on : HD-TV, SD-TV
TECHNIROUTER ready : Yes
TUNER - SAT
Reception range : 950 ... 2.150 MHz
Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
DVB-S : QPSK
DVB-S : 2 ... 45
DVB-S2 : 8PSK - QPSK
DVB-S2 : 10 ... 31
FEC : RS, LDPC, BCH

DIGIDISH 45, Universal-Twin-LNB

ARTICLE INFORMATION
EAN : 4019588452824
Item no. : 1045/2882
Colour : beige
Weight (Box) : 3,7 kg
Weight : 2,9 kg
Device (W x H x D) : 45 x 48 cm
Box : 51 x 51 x 23 cm
LOCAL OSCILLATOR
Low band : 9,75 GHz
High band : 10,7 GHz
LNB CONTROL
Vertical : 11,5 - 14 V

Horizontal : 16 - 19 V
Band switch : 22 kHz
GENERAL CHARACTERISTICS
Material : Aluminium
Material strength : 1 mm
Coating : Powder-coated on both sites
including Wall bracket : Yes
INPUT FREQUENCY RANGE
Low band : 10,7 ... 11,7 GHz
High band : 11,7 ... 12,75 GHz
NOISE FACTOR
Lower frequency range : 0,7 dB max.
Upper frequency range : 0,7 dB max.

OUTPUT FREQUENCY RANGE
Low band : 950 - 1.950 MHz
High band : 1.100 - 2.150 MHz
POWER SUPPLY
LNB voltage supply : 11,5 ... 19 V
Power consumption : max. 190 mA
TECHNICAL DATA
F/D : 0,6
Offset angle : 30 °
Gain : 32,2 dBi @11,3 GHz
Feed reception : 40 mm

black/white
black/white