



DIGIT ISIO S

Digital HDTV satellite receiver with internet functionality

EAN	Item no.	Colour	Hard drive	Weight (Box)	Weight	Device (W x H x D)	Box
4019588147522	0001/4752	silver	extern	2,9 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm
4019588047525	0000/4752	black	extern	2,9 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm

TOP FEATURES

HDTV-Twin-Tuner

Digitale Videorekorder-Funktion via USB (DVRready)

IP-Modul für Zugriff auf Mediatheken, Video on Demand Dienste und Apps

Freies Browsen, HbbTV und ISIO Live! (TechniSat Service Portal)

Inklusive HD+ Karte, sowie 2 CI+ Schnittstellen (kompatibel zu Sky)

UPnP/DLNA/Client- & Serverfunktion im Heimnetzwerk

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 - 35 °C

Humidity : 10 - 75 %

LNB CONTROL

Horizontal : 18 V

Band switch : 22 kHz

DiSEqC : DiSEqC 1.0 / DiSEqC 1.2 Sat Channel Router

Vertical : 14 V

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HbbTV : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

eSATA : Yes

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

F socket : 2

DECRYPTION SYSTEM

Conax : Yes

Nagravision : Yes

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

576i : Yes

576p : Yes

SD : Yes

720p : Yes

1080i : Yes

HD : Yes

GENERAL CHARACTERISTICS

Hard drive : extern

HANDLING/COMFORT

Sleep timer : Yes

Alarm : Yes

OTHER FEATURES

OSD languages : German, Russian, Greek, Spanish, Polish, Italian, Czech, Hungarian, Swedish, Portuguese, Dutch, French, Turkish, English

Total programme memory : 5.000

POWER CONSUMPTION

Standby LED : < 0,3 W

In operation : 11,5 W

POWER SUPPLY

Nominal voltage : 180 ... 250 V

Frequency : 50 Hz

Mains adapter : internal

READY FOR RECEPTION

HD+ : Yes

SUPPORTED FORMATS & CODECS

Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX

Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI

JPEG : Yes

Audio-Formats : AAC, MP3, M4A, MP2

TUNER	TUNER - SAT	SCOPE OF DELIVERY
Tuner type : DigitalSat	DVB-S2 : 8PSK-QPSK	DIGIT ISIO S International Edition, Remote control with batteries, Power cable, HDMI cable, Instruction manual
DVB-S tuner : 2	FEC : Viterbi and Reed-Solomon	
Input impedance : 75 Ω	DVB-S : 2 ... 45	
Reception on : HDTV (Mpeg-4+2)	DVB-S2 : 10 ... 31	
TECHNIROUTER ready : Yes	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8	
 The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.		Reception range : 950 ... 2,150 MHz