



DIGICORDER ISIO S1

Digital HDTV satellite receiver with internet functionality

EAN	Item no.	Colour	Hard drive	Weight (Box)	Weight	Device (W x H x D)	Box
4019588517264	0501/4726	silver	500 GigaByte	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
4019588507265	0500/4726	black	500 GigaByte	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
4019588117266	1001/4726	silver	1.000 GigaByte	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm
4019588107267	1000/4726	black	1.000 GigaByte	3,3 kg	2,9 kg	43,5 x 6 x 19,9 cm	49 x 16 x 26 cm

TOP FEATURES

UPnP/DLNA/Client- & Server function for home networking

2 CI+ interface (compatible with HD and Sky+)

Free browsing, and HbbTV ISIO Live! (TechniSat Service Portal)

IP module for access to libraries, Video on demand services and apps

Integrated hard drive (1 TB)

HDTV Twin Tuner

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : 5 ... 35 °C

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

INTERNET/NETWORK

HTML 5 support : Yes

HbbTV : Yes

CARD READER

SD card : Yes

CONNECTIONS

HDMI™ (out) : 1

Digital electric audio output (S/PDIF) : Yes

Digital optical audio out : Yes

Audio out analogue (RCA) : Yes (rechts / links)

YUV (component output) : 1

Scart : 1

Video Cinch out : 1

Ethernet 10/100 (RJ-45) : Yes

F socket : 2

DECRYPTION SYSTEM

Conax : Yes

CI+ : Yes

DISPLAY

Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)

Freeze frame : Yes

Zoom : Yes

576i : Yes

576p : Yes

SD : Yes

HD : Yes

720p : Yes

1080i : Yes

HANDLING/COMFORT

Sleep timer : Yes

Alarm : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

OTHER FEATURES	SUPPORTED FORMATS & CODECS	TUNER
OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX	Tuner type : DigitalSat
Total programme memory : 5.000	Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI	DVB-S tuner : 2
Regional channel selection : Yes	JPEG : Yes	Single Cable Solution (SatCR) : SCR1 = EN50494
POWER CONSUMPTION	Audio-Formats : AAC, MP3, M4A, MP2	Reception on : HDTV (MPEG-4 & 2), SD (MPEG-2)
Standby fast start : 6,9 W		Input impedance : 75 Ω
Standby LED : 0,25 W		TECHNIROUTER ready : Yes
In operation : 13 W		TECHNISELECT 12 ready : Yes
POWER SUPPLY		TUNER - SAT
Nominal voltage : 230 V		Reception range : 950 ... 2.150 MHz
Frequency : 50 Hz		Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
Mains adapter : internal		DVB-S : QPSK
		DVB-S : 2 ... 45
		DVB-S2 : 8PSK-QPSK
		DVB-S2 : 10 ... 31
		FEC : Viterbi and Reed-Solomon
		SCOPE OF DELIVERY
		DigiCorder ISIO S1, remote control including batteries, mains cable, HDMI cable, operating instructions, guarantee card



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.