



DIGIT ISIO S

HDTV satellite receiver with Twin-Tuner, Internet access and DVR functionality via USB for the record of TV and radio channels to an external HDD

EAN	Colour	Item no.	Hard drive	Weight (Box)	Weight	Device (W x H x D)	Box
4019588647534	black	0006/4753	extern	2,6 kg	1,6 kg	31 x 5,2 x 20 cm	37 x 15,2 x 26,5 cm

TOP FEATURES

HDTV-Twin-Tuner	Free browsing, HbbTV (if provided by your broadcaster) and ISIO Live! (TechniSat Service Portal)	Unterstützt Audio Codierformat AAC
Digital video recorder via USB (DVRready)	2 Common Interface CI+	
IP module for access to media libraries and video on demand services	UPnP / DLNA / Client- & server function for home networking	
MULTIMEDIA	Internet speed test : Yes	Freeze frame : Yes
DVR function : USB	ISIO live : Yes	Zoom : Yes
Timeshift : Yes	HbbTV : Yes	SD : Yes
AMBIENT OPERATING CONDITIONS	CARD READER	HD : Yes
Ambient temperature : 5 ... 35 °C	SD card : Yes	1080i : Yes
Humidity : 10 ... 75 %	CONNECTIONS	720p : Yes
LNB CONTROL	HDMI™ (out) : 1	HANDLING/COMFORT
Vertical : 14 V	USB : 3 (USB 2.0)	Media Player : Yes
Horizontal : 18 V	eSATA : Yes	Alarm : Yes
Band switch : 22 kHz	Digital electric audio output (S/PDIF) : Yes	Sleep timer : Yes
Current consumption : max. 400 mA (kurzschlussfest)	Digital optical audio out : Yes	HOTEL MODE
DiSEqC : 1.0 / 1.2	Audio out analogue (RCA) : Yes (rechts / links)	Protected access to hotel mode : Yes
TECHNISAT ADDED VALUE SERVICES	YUV (component output) : 1	Customisable start screen : Yes
ISIPRO : Yes	Scart : 1	Lockable volume : Yes
AUTOINSTALL : Yes	Video Cinch out : 1	Menu locking : Yes
TECHNIMATIC : Yes	Ethernet 10/100 (RJ-45) : Yes	Control panel lock : Yes
SFI : Yes	F socket : 2	Integrated LED clock : Yes
TECHNIFAMILY : Yes	DECRYPTION SYSTEM	Selectable start source : Yes
INTERNET/NETWORK	Conax : Yes	Selectable start channel : Yes
ISIO Internet : Yes	CI+ : Yes	
Webbrowser : Yes	DISPLAY	
HTML 5 support : Yes	Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	

OTHER FEATURES	SUPPORTED FORMATS & CODECS	TUNER
OSD languages : German, Bulgarian, English, French, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Slovakian, Swedish, Spanish, Czech	Video-Codecs : MPEG-2, MPEG-4, MPEG-1, H.264, DivX	Tuner type : DigitalSat
Total programme memory : 5.000	Video-Formats : MKV, MP4, MOV, TS, TS4, VOB, WMV, Xvid, AVI	DVB-S tuner : 2
POWER CONSUMPTION	JPEG : Yes	Single Cable Solution (SatCR) : SCR1 = EN50494
Standby fast start : 6,5 W	Audio-Formats : AAC, MP3, M4A, MP2	Reception on : HDTV (MPEG-4 & 2), SD (MPEG-2)
Standby LED : < 0,2 W	TECHNISAT CONNECT	TECHNISELECT 12 ready : Yes
In operation : 11,05 W	Control : Yes	TECHNIROUTER ready : Yes
POWER SUPPLY	SFI : Yes	TUNER - SAT
Nominal voltage : 230 V		Reception range : 950 ... 2.150 MHz
Frequency : 50 Hz		Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
Mains adapter : internal		DVB-S : QPSK
		DVB-S : 2 ... 45
		DVB-S2 : 8PSK-QPSK
		DVB-S2 : 10 ... 31
		FEC : Viterbi and Reed-Solomon
		SCOPE OF DELIVERY
		DIGIT ISIO S INTERNATIONAL EDITION, Remote Control TECHNICONROL with batteries, Power Cable, HDMI Cable, Instruction Manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.